
一、性能特点 Characteristics:

1. 常誉隆减速机是在模块组合体系的基础上设计的，可以方便地配用各种型式的电动机或采用其他动力输入。同种机型可配用多种功率的电动机。容易实现各种机型之间的组合联接。
2. 传动效率高，单机型减速机效率高达96%。
3. 传动比划分细，范围广。组合机型可以形成较大的传动比，输出转速低。
4. 安装形式多样，可任意位置卧式或法兰安装。
1. XIDALI reducers are based on the building block design, so it's convenient for them to fit all types of motors or to connect with other power input. The same type of reducers can fit motors with different power, so that it's possible for different types of machines to combine or connect.
2. High transmission efficiency. A single machine can reach a transmission efficiency as much as 96%.
3. Precise division of transmission ratio with a wide range. The combination of machines can produce a larger transmission ratio at a low output rotational speed.
4. Various ways of installation. Horizontal installation at any position or flanged installation.


二、场所条件 Working Environment:

1. 环境温度-40℃~50℃。（0℃以下启动时润滑油要加热到0℃以上。）
2. 海拔不超过1000米。
3. 输入转速不大于1800rpm，齿轮最高圆周速度不超过22m/s。
4. 可用于正反运转。
5. 无行业限制。
6. 其他条件下使用请与我公司技术部联系。
1. Working temperature: -40℃~50℃ (The lubrication should be heated until above 0℃ if the machine works Below 0℃)
2. The working place should be lower than 1,000 meters above sea level.
3. The input rotational speed should not exceed 1,800r/m. The circumferential speed of the gear should not exceed 20m/s.
4. Suitable for normal-reverse rotation.
5. Without industry limitation.
6. Please consult our technical supporting department for other circumstances.

三、选型指南 Instructions for Selection:

在确定使用系数之前必须先确定一天的运行小时数，每小时的起停次数和负载类型。其中负载类型按下列公式计算：

The daily operating time, the starting frequency and the load classifications be determined before deciding the service factor, The load classifications is calculated with the following formula:



负载类型 Load classification

- | | |
|------------------------------|---|
| I 均匀负载, 惯性加速系数 ≤ 0.2 | Uniform load, mass acceleration factor ≤ 0.2 |
| II 中等冲击负载, 惯性加速系数 ≤ 3 | Medium Impact Load, mass acceleration factor ≤ 3 |
| III 强烈冲击负载, 惯性加速系数 ≤ 10 | Heavy shock Load, mass acceleration factor ≤ 10 |

如果惯性加速系数 > 10 , 请与我公司技术部联系。

$$\text{惯性加速系数} = \frac{\text{所有外部转动惯量}}{\text{驱动电机的转动惯量}}$$

实际的工况系数 f_A 必须满足下式: 使用系数 $f_B \geq \text{工况系数 } f_A$

使用系数 f_B 已在后面的选型参数表中列出。

允许的轴伸径向载荷及轴向载荷

输出轴端允许的径向载荷及轴向载荷资料, 请与我公司技术部联系。

减速机的使用与维护请参阅随机附带的《减·变速器使用说明书》。

Please contact our technical supporting department in case the mass acceleration factor > 10 .

$$\text{Mass acceleration factor} = \frac{\text{All external mass moments of Inertia}}{\text{Mass moment of inertia on the motor end}}$$

The actual operating mode factor (f_A) should meet the following formula:

$$\text{service factor } f_B \geq \text{operating mode factor } f_A$$

The service factor f_B is listed in the parameter selection list.

The permitted overhung loads and the axial forces.

Please contact our technical supporting department for the information on the permitted overhung loads and the axial forces at the output end of the shaft.

Regarding the use and maintenance of the reductor, please refer to the attached Instruction Manual of the Reductor and the Variable Speed Motor.

减速机在投入运行前必须加入适当粘度的润滑油，须使齿轮间摩擦减速机，遇高负荷及冲击负荷时，减速机才能充分发挥其机能。

首次使用200小时左右，必须将润滑油放掉，冲洗干净，然后重新加入新的润滑油至油标中心，油位过高或过低都可能导致运转温度升高。

(详细操作过程请参数安装，使用与维护有关条例的内容)

推荐润滑油牌号：


Reducer proper viscosity lubricating oil must be added before putting into operation, must make the friction between the gear reducer, meet the high load and impact load, the speed reducer can give full play to its function.

Was first used 200 hours, must put out the lubricating oil, rinse, then rejoined the new oil to the center, oil level too high or too low can lead to working temperature.

(for the detailed procedure, please install, use and maintain the contents of the relevant regulations)


Recommended lubricants brand number:

润滑油类型 Lubrication type	油润滑 Oil				脂润滑 Grease	专用润滑油 Special Lubricants	
环境温度 (°C) Ambient temperature °C	+40 to 0	+25 to-15	+10 to-30	-20 to-50	+40 to-15	-40 to+80	-40 to+10
ISO 粘度 ISO viscosity class	VG 220	VG 150 VG 100	VG 68-46 VG 32	VG 22 VG 15		VG 220	VG 32
	BP Energol GR-XP220	BP Energol GR-XP100	BP Energol GR-XP68	BP Energol LPT 22	BP Energrease HT-EP 00		
	Mobilgear 630	Mobilgear 629	Mobil D.T.E 15M	Mobil D.T.E 11M	Mobilplex 44	Mobil SHC 630	Mobil SHC 624
	Shell Omala Oil 220	Shell Omala Oil 100	Shell Tellus Oil T32	Aero Shell Fluid 41	Shell Grease S 3655		




注：1 四大系列带胀紧套减速机除输出轴不同外，其余均同平键空心轴标准产品

Note: 1 Except the output shaft, the main four series gear units with shrink disk are the same as the standard ones with hollow shafts with flat key.



注：1.四大系列带胀紧盘减速机除输出轴不同外，其余均同平键空心轴标准产品

Note:1 Except the output shaft, the main four series gear units with shrink disk are the same as the standard ones with hollow shafts with plat key.




电机 机座号	4级 Class4		6级 Class6		8级 Class8		L3				安 装 尺 寸 Mounting dimensions										M(kg)			
	P ₁ (kW)	n ₁ (r/min)	P ₁ (kW)	n ₁ (r/min)	P ₁ (kW)	n ₁ (r/min)	Y ₂	B	YEJ	YVP	M	N	P	n	T	d	E	b	c	Y (铝壳) (Aluminum housing)	Y ₂	B	YEJ	YVP
63	0.12	1390					202	270	328		115	95j6	140	4×Φ10	3	11j6	23	4	8.5	5.5	13			11
	0.18	1390																		6	13.5	15		12
71	0.25	1390	0.18	850			225	285	345		130	110j6	160	4×Φ10	3.5	14j6	30	5	11	6.5	14	16	12	14
	0.37	1390	0.25	850																7.5	14.5	16	13	15
80	0.55	1390	0.37	885	0.18	645	255	290	350	310	165	130j6	200	4×Φ12	3.5	19j6	40	6	15.5	10	15	31	20	16
	0.75	1390	0.55	885	0.25	645														11	16	32	21	17
90S	1.1	1400	0.75	910	0.37	670	270	310	370	320	165	130j6	200	4×Φ12	3.5	24j6	50	8	20	16	23	35	27	23
90L	1.5	1400	1.1	910	0.55	670	295	335	395	345	165	130j6	200	4×Φ12	3.5	24j6	50	8	20	20	25	39	31	28
100	2.2	1420			0.75	680	325	370	420	370	215	180j6	250	4×Φ15	4	28j6	60	8	24		33	49	41	35
	3	1420	1.5	920	1.1	680															35	53	44	36
112M	4	1440	2.2	940	1.5	690	340	400	450	390	215	180j6	250	4×Φ15	4	28j6	60	8	24		41	67	60	43
132S	5.5	1440	3	960	2.2	710	390	430	505	450	265	230j6	300	4×Φ15	4	38k6	80	10	33		65	93	85	63
132M	7.5	1460	4	960	3	710	430	470	545	490	265	230j6	300	4×Φ15	4	38k6	80	10	33		76	105	98	75
			5.5	960																				
160M	11	1460	7.5	960	4	720	505	545	610	550	300	250h6	350	4×Φ19	5	42k6	110	12	37		118	150	143	116
					5.5	720																		
160L	15	1460	11	960	7.5	720	560	585	655	595	300	250h6	350	4×Φ19	5	42k6	110	12	37		132	169	165	136
180M	18.5	1470					590	620	715	740	300	250h6	350	4×Φ19	5	48k6	110	14	42.5		164	205	203	169
180L	22	1470	15	970	11	730	630	640	765	790	300	250h6	350	4×Φ19	5	48k6	110	14	42.5		182	222	216	183
200	30	1470	18.5	970	15	730	660	695	790	850	350	300h6	400	4×Φ19	5	55k6	110	16	49		245	300	296	236
			22	970																				
225S	37	1480			18.5	730	675	705	860	910	400	350h6	450	8×Φ19	5	60m6	140	18	53		258	360	370	291
225M	45	1480	30	980	22	730	705	730	890	940	400	350h6	450	8×Φ19	5	60m6	140	18	53		290	390	405	327
250	55	1480	37	980	30	730	770	795		1060	500	450h6	550	8×Φ19	5	65m6	140	18	58		388	530	498	393
280S	75	1480	45	980	37	730	845	870		1160	500	450h6	550	8×Φ19	5	75m6	140	20	67.5		510	660	633	520
280M	90	1485	55	980	45	740	895	920		1260	500	450h6	550	8×Φ19	5	75m6	140	20	67.5		606	785	723	610
315S	110	1485	75	980	55	740	1100	1100		1330	600	550h6	660	8×Φ24	6	80m6	170	22	71		910	1000	1150	950
315M	132	1485	90	985	75	740	1180	1180		1380	600	550h6	660	8×Φ24	6	80m6	170	22	71		1000	1100	1230	1030
315L	160	1485	110	985	90	740	1270	1270						8×Φ24	6	80m6	170	22	71		1055	1100	1320	1100
	200	1485	132	985	110	740																		
																					1128	1160	1420	1200

注：由于结构需要及生产厂家不同，有时参数会有所变化，此表仅供参考，准确尺寸请来电垂询。


Note: Sometimes the parameters may be changed with the different structures and manufacturers, this table is only for reference, please refer to us for the exact dimensions.

R 系列斜齿轮减速机 R series helical gear motor


[系列产品]
series of products




R系列减速机有以下设计方案：
R series gear units are available
in the following designs:




RM...
搅拌机专用减速机
Specially for stirrer drives




R...Y...
底脚轴伸式安装斜齿轮减速机
Foot-mounted helical gear
units with solid shaft




RF...Y...
法兰轴伸式安装斜齿轮减速机
Flange-mounted helical gear
units with solid shaft




RS...
底脚轴伸式安装，轴输入的斜齿轮减速机
Foot-mounted, shaft input helical gear
units with solid shaft




RFS...
法兰轴伸式，轴输入为斜齿轮减速机
Flange-mounted, shaft input helical
gear units with solid shaft




R...RF...Y...
底脚轴伸式安装组合型斜齿轮减速机
Foot-mounted combinatorial helical
gear units with solid shaft




RF...RF...Y...
法兰轴伸式组合型斜齿轮减速机
Flange-mounted combinatorial
helical gear units with solid shaft




RS...RF...
底脚轴伸式安装组合型，轴输入的
斜齿轮减速机
Foot-mounted combinatorial
shaft input helical gear units
with solid shaft




RFS...RF...
法兰轴伸式组合型，轴输入的
斜齿轮减速机
Flange-mounted combinatorial,
shaft input helical units with
solid shaft




RX...Y...
底脚轴伸式安装单级斜齿轮减速机
Foot-mounted single-stage helical
gear units with solid shaft



RXF...Y...
法兰轴伸式安装单级斜齿轮减速机
Flange-mounted single-stage
helical gear units with solid shaft







RXS...
底脚轴伸式安装，轴输入的单级
斜齿轮减速机
Foot-mounted, shaft input single
-stage helical gear units with
solid shaft





RXFS...
法兰轴伸式，轴输入的单级斜齿轮减速机
Flange-mounted, shaft input single
-stage helical gear units with solid
shaft

型号与标记 Type Designations:

R 37- Y 0.55-4P-32.40-M1-0° φ 200 减速机类型 结构形式 规格 电机代号 电机功率、极数 传动比 安装形式 电机接线盒位置 输出法兰外径	R 37- Y 0.55-4P-32.40-M1-0° φ 200 Gear units type Structure Size Motor code Motor power、 pole Ratio Mounting position Position of the motor thermal box Outer diameter of output flange
减速机类型: 斜齿轮硬齿面减速机	Gear units type: rigid tooth flank helical gear units
结构形式: 普通轴伸式 (省略) 轴伸法兰式 F 普通轴伸式, 轴输入 S 轴伸法兰式, 轴输入 FS 搅拌机专用 M	Structure: Foot-mounted solid shaft output (---) Flange-mounted solid shaft output F Foot-mounted solid shaft output shaft input S Flange-mounted solid shaft output, shaft input FS Specially for stirrer M
规格: (见选型参数表)	Size: (see selection table)
电机代号: 普通(更新) Y(Y2) 防爆 B 直流 Z 制动 E 多速 D 变频 V 分马力 F 增安 A 电磁调速 C 冶金起重 R 变频制动 VE 辊道 G	Motor code: Ordinary(renew) Y(Y2) Flame-proof B Direct current Z Brake E Multi-speed D Variable frequency V Power-divided F Ampere-increased A Electromagnetism speed modulation C Hoisting in metallurgy R Variable frequency and brake VE Roller tables G
电机功率、极数: (见选型参数表)	Motor power、 pole: (see selection table)
传动比: (见选型参数表)	Ratio: (see selection table)
安装形式: M1、M2、M3、M4、M5、M6(见第10页)	Mounting position: M1、M2、M3、M4、M5、M6(see page10)
电机接线盒位置: 0° 90° 180° 270°(见第9页)	Position of the motor thermal box: 0° 90° 180° 270°(see page9)
输出法兰外径: (见外型安装尺寸图) 底脚安装时省略	Outer diameter of output flange: (See the chart of mouting dimension sheets-overview) It will be omitted when foot mouting.
电机接线盒位置: Position of the motor thermal box:  0°  90°  180°  270°	

安装形式：
Mounting position:



输入功率及最大转矩*
Input power rating and maximum torque

规格 Size	17	27	37	47	57	67	77	87	97	107	137	147	167
结构形式 Structure	R						RF						
输入功率 Input power rating (kw)	0.18~0.75	0.18~3	0.18~3	0.18~5.5	0.18~7.5	0.18~7.5	0.18~11	0.55~18.5	0.55~30	2.2~45	5.5~55	11~90	11~160
传动比 Ratio	3.83~ 74.84	3.37~ 135.09	3.33~ 134.82	3.83~ 176.88	4.39~ 186.89	4.29~ 199.81	5.21~ 195.24	5.36~ 246.54	4.49~ 289.74	5.06~ 249.16	5.15~ 222.60	5.00~ 163.31	10.24~ 229.71
最大转矩* Maximum torque (N.m)	85	130	200	300	450	600	820	1550	3000	4300	8000	13000	18000

规格 Size	37	57	67	77	87	97	107	127	157
结构形式 Structure	RX				RXF				
输入功率(kw) Input power rating	0.18~1.1	0.18~5.5	0.18~7.5	1.1~11	3~22	5.5~30	7.5~45	7.5~90	11~132
传动比 Ratio	1.62~4.43	1.3~5.5	1.4~6.07	1.42~6.00	1.39~6.65	1.42~6.23	1.44~6.63	1.51~6.2	1.57~6.2
最大转矩*(N.m) Maximum torque	20	70	135	215	400	600	830	1110	1680

减速机重量
Gear unit weight

规格 Size	R17	R27	R37	R47	R57	R67	R77	R87	R97	R107	R137	R147	R167
重量(kg) Weight	4	5.5	8.5	10	18	25	36	63	101	153	220	400	700
机型号 Gear unit type	RX37	RX57	RX67	RX77	RX87	RX97	RX107	RX127	RX157				
重量(kg) Weight	5	8	14	23	39	70	100	150	250				

所注重量为平均值, 仅供参考

*) 最大转矩系指该规格不同传动比对应的最大转矩中的最大值

The weights are mean values, only for reference.

*) Maximum torque means the biggest one of the maximum torque related to the different ratio for the specified size.

RM减速机选型

选择最小使用系数

$$f_{Amin}=1.5 \text{ for } L_{10h} \geq 10000h$$

$$f_{Amin}=2.0 \text{ for } L_{10h} \geq 25000h$$

其它要求

根据最小使用系数选择齿箱规格

$$f_{Amin} \leq f_B$$

校核径向载荷 (轴承)

$$F_r \leq F_{XL} = F_{Ra} \cdot a/(x+b)$$

a、b—换算系数

F_r —运行时的径向载荷

F_{Ra} —许用径向载荷

校核轴向载荷

$$F_a \leq F_{Aa}$$

F_a —运行时的径向载荷

F_{Aa} —许用轴向载荷

RM Gear Units Selection

Select minimum service factors

$$f_{Amin}=1.5 \text{ for } L_{10h} \geq 10000h$$

$$f_{Amin}=2.0 \text{ for } L_{10h} \geq 25000h$$

Other requirements

Select gear units size based on minimum service factor

$$f_{Amin} \leq f_B$$

Check overhung load (Bearing)

$$F_r \leq F_{XL} = F_{Ra} \cdot a/(x+b)$$

a、b—Conversion factor

F_r —Overhung load during operation

F_{Ra} —Permitted overhung load

Check axial load

$$F_a \leq F_{Aa}$$

F_a —Axial load during operation

F_{Aa} —Permitted axial load

许用径向载荷 $F_{Rr}(X=1000mm)$


Permitted overhung loads F_{Rr} at $X=1000mm$

型号 Size	RM67	RM77	RM87	RM97	RM107	RM137	RM147	RM167
F_{Rr} (N)	580	1200	1950	3000	4230	7500	11000	14600

计算径向载荷 $F_{XL}(X \neq 1000mm)$ 的换算系数

Conversion factors to calculate the permitted overhung loads F_{XL} at $X \neq 1000mm$

型号 Size	RM67	RM77	RM87	RM97	RM107	RM137	RM147	RM167
a	1047	1050	1056.5	1061	1069	1088	1091	1089.5
b	47	50	56.5	61	69	88	91	89.5



许用轴向载荷FAa，根据不同的使用系数fA和不同的额定轴承使用寿命L10h提供

Permitted axial loads FAa, Provided according to various service factor fA and nominal bearing service life L10h

FAmin=1.5/L10h=10000h									
型号 Size		n2(r/min)							
		<16	16-25	26-40	41-60	61-100	101-160	161-250	251-400
RM67	FAa(N)	19000	18900	15300	11900	9210	7470	5870	5050
RM77	FAa(N)	22000	22000	19400	15100	11400	9220	7200	6710
RM87	FAa(N)	30000	30000	23600	18000	14300	11000	8940	8030
RM97	FAa(N)	40000	36100	27300	20300	15900	12600	9640	7810
RM107	FAa(N)	48000	41000	30300	23000	18000	13100	9550	9030
RM137	FAa(N)	70000	70000	70000	57600	46900	44000	35600	32400
RM147	FAa(N)	70000	70000	69700	58400	45600	38000	32800	30800
RM167	FAa(N)	70000	70000	70000	60300	45300	36900		

FAmin=2.0/L10h=25000h									
型号 Size		n2(r/min)							
		<16	16-25	26-40	41-60	61-100	101-160	161-250	251-400
RM67	FAa(N)	15800	12000	9580	7330	5580	4460	3460	2930
RM77	FAa(N)	20000	15400	11900	9070	6670	5280	4010	3700
RM87	FAa(N)	24600	19200	14300	10600	8190	6100	5490	4860
RM97	FAa(N)	28400	22000	16200	11600	8850	6840	5830	4760
RM107	FAa(N)	32300	24800	17800	13000	9780	8170	5950	5620
RM137	FAa(N)	70000	59900	48000	37900	33800	31700	25600	23300
RM147	FAa(N)	70000	60600	45900	39900	33500	27900	24100	22600
RM167	FAa(N)	70000	63500	51600	37800	26800	23600		

润滑油量表
Lubrication table

规格 Size	润滑油量(升)			Fill quantity in liters		
	M1 1)	M2 1)	M3	M4	M5	M6
R17	0.25	0.6	0.35	0.6	0.35	0.35
R27	0.25/0.4	0.7	0.4	0.7	0.4	0.4
R37	0.3/1	0.9	1	1.1	0.8	1
R47	0.7/1.5	1.6	1.5	1.7	1.5	1.5
R57	0.8/1.7	1.9	1.7	2.1	1.7	1.7
R67	1.1/2.3	2.6/3.5	2.8	3.2	1.8	2
R77	1.2/3	3.8/4.3	3.6	4.3	2.5	3.4
R87	2.3/6	6.7/8.4	7.2	7.7	6.3	6.5
R97	4.6/9.8	11.7/14	11.7	13.4	11.3	11.7
R107	6/13.7	16.3	16.9	19.2	13.2	15.9
R137	10/25	28	29.5	31.5	25	25
R147	15.4/40	46.5	48	52	39.5	41
R167	27/70	82	78	88	66	69

规格 Size	润滑油量(升)			Fill quantity in liters		
	M1 1)	M2 1)	M3	M4	M5	M6
RF17	0.25	0.6	0.35	0.6	0.35	0.35
RF27	0.25/0.4	0.7	0.4	0.7	0.4	0.4
RF37	0.4/1	0.9	1	1.1	0.8	1
RF47	0.75/1.5	1.6	1.5	1.7	1.5	1.5
RF57	0.8/1.7	1.8	1.7	2	1.7	1.7
RF67	1.2/2.5	2.7/3.6	2.7	3.1	1.9	2.1
RF77	1.2/2.6	3.8/4.1	3.3	4.1	2.4	3
RF87	2.4/6	6.8/7.9	7.1	7.7	6.3	6.4
RF97	5.1/10.2	11.9/14	11.2	14	11.2	11.8
RF107	6.3/14.9	15.9	17	19.2	13.1	15.9
RF137	9.5/25	27	29	32.5	25	25
RF147	16.4/42	47	48	52	42	42
RF167	26/70	82	78	88	65	71

规格 Size	润滑油量(升)			Fill quantity in liters		
	M1	M2	M3	M4	M5	M6
RX37/RXF37	0.45/0.4	0.6	1.1/0.9	1.1/0.9	0.7/0.6	0.7/0.6
RX57/RXF57	0.6/0.5	0.8	1.3/1.1	1.3/1.1	0.9/0.7	0.9/0.7
RX67/RXF67	0.8/0.7	0.8	1.7/1.5	1.9/1.7	1.1/1	1.1/1
RX77/RXF77	1.1/0.9	1.5	2.6/2.4	2.7/2.5	1.6	1.6
RX87/RXF87	1.7/1.6	2.5	4.8/4.9	4.8/4.7	2.9	2.9
RX97/RXF97	2.1	3.4/3.6	7.4/7.1	7	4.8	4.8
RX107/RXF107	3.9/3.1	5.6/5.9	11.6/11.2	11.9/10.5	7.7/7.2	7.7/7.2
RX127/RXF127	5.6/5.9	11.6/11.2	21.9/20.5	22.7/22.2	9.7/9.2	9.7/9.2
RX157/RXF157	11.6/11.2	21.9/20.5	31.3/30.5	32.7/32.2	13.2/12.7	13.2/12.7

注: 1) 表示减速机为组合型时低速级所加油量为大值。

Notes: 1) The large gear unit of multi-stage gear units must be filled with the larger oil volume.

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
0.18kW						0.18kW					
0.16	9293	8443	1.31	R 147R77 RF147R77	4	1.6	944	858	0.82	R 77R37 RF77R37	4
0.19	8042	7307	1.52		4	1.7	904	821	0.85		
0.22	7096	6447	1.72			1.8	833	757	0.93		
0.25	6128	5568	1.99			1.9	803	730	0.96		
0.29	5300	4815	2.31			2.1	739	671	1.04		
0.32	4760	4325	2.57			2.2	711	646	1.08		
0.38	4038	3669	3.03			2.4	628	571	1.23		
0.43	3553	3228	3.44			2.5	602	547	1.28		
0.16	9668	8784	0.80	R 137R77 RF137R77	4	2.9	525	477	1.47		
0.19	8232	7479	0.91		4	3.3	469	426	1.64		
0.22	7057	6412	1.07			3.8	402	365	1.92		
0.24	6421	5834	1.17			4.5	341	310	2.26		
0.28	5504	5001	1.37			2.4	628	571	0.90	R 67R37 RF67R37	4
0.30	5183	4709	1.45			2.5	617	561	0.91		
0.32	4803	4364	1.57			2.9	532	483	1.06		
0.35	4323	3928	1.74			3.2	482	438	1.17		
0.40	3868	3514	1.94			3.6	427	388	1.32		
0.42	3674	3338	2.05			4.1	370	336	1.53		
0.47	3224	2929	2.33			4.8	316	287	1.79		
0.31	4881	4435	0.83	R 107R77 RF107R77	4	5.5	281	255	2.01		
0.36	4260	3870	0.95		4	3.0	518	471	0.82	R 57R37 RF57R37	4
0.42	3634	3302	1.11			3.1	488	443	0.87		
0.46	3299	2997	1.23			3.4	451	410	0.94		
0.53	2885	2621	1.40			3.9	395	359	1.07		
0.62	2479	2252	1.63			4.3	357	324	1.19		
0.68	2246	2041	1.80			4.4	351	319	1.20		
0.71	2169	1971	1.86			4.8	319	290	1.33		
0.77	1995	1813	2.03			5.2	294	267	1.44		
0.88	1747	1587	2.31			5.3	288	262	1.47		
1.0	1529	1389	2.64			5.7	271	246	1.56		
1.1	1338	1216	3.02			5.8	265	241	1.59		
0.51	2996	2722	0.94	R 97R57 RF97R57	4	6.3	242	220	1.75	R 47R37 RF47R37	4
0.52	2937	2668	0.96		4	6.5	237	215	1.79		
0.60	2544	2311	1.11			7.4	207	188	2.04		
0.62	2471	2245	1.14			8.7	175	159	2.42		
0.67	2287	2078	1.23			4.6	331	301	0.85		
0.69	2219	2016	1.27			5.5	281	255	1.00		
0.80	1907	1733	1.48			6.1	251	228	1.12		
0.86	1786	1623	1.58			7.1	215	195	1.31		
0.97	1578	1434	1.79			6.2	249	226	0.80	R 37R17 RF37R17	4
1.2	1328	1207	2.12			6.9	222	202	0.85		
1.3	1193	1084	2.36			7.0	219	199	0.86		
1.5	1028	934	2.74			7.8	197	179	0.95		
1.6	966	878	2.92			8.9	173	157	1.09		
1.8	831	755	3.39			9.1	172	156	1.11		
0.79	1912	1737	0.80	R 87R57 RF87R57	4	9.3	165	150	1.14		
0.80	1907	1733	0.85		4	9.9	155	141	0.80	R 27R17 RF27R17	4
0.91	1677	1524	0.87			10	149	135	0.82		
0.93	1639	1489	0.89			11	136	124	0.90		
1.0	1535	1395	0.95			12	130	118	0.94		
1.1	1356	1232	1.07			13	121	110	1.01		
1.2	1260	1145	1.16			14	114	104	1.07		
1.3	1141	1037	1.28			15	103	94	1.18		
1.4	1034	1003	1.32			4.4	371	195.24	2.1	R 77 RF77	6
1.5	1025	931	1.42			5.1	317	166.59	2.4		
1.6	972	883	1.50			5.8	277	145.67	2.8		
1.7	883	802	1.65			6.1	263	138.39	2.9		
1.8	852	774	1.71			7.0	231	121.42	3.3		

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p
0.18kW						0.18kW					
7.1	227	195.24	3.4	R 77 RF77	4	11	144	123.91	0.85	R 27 RF27	4
8.3	194	166.59	4.0		4	13	123	105.49	1.00		
9.5	169	145.67	4.6		4	15	106	90.96	1.16		
10	161	138.39	4.8		4	16	99	84.78	1.24		
4.3	380	199.81	1.48	R 67 RF67	6	19	86	74.11	1.42		
4.6	350	184.07	1.61			20	81	69.47	1.51		
5.4	301	158.14	1.88			23	71	61.30	1.71		
6.2	262	137.67	2.2			25	65	55.87	1.88		
6.6	245	128.97	2.3			29	56	48.17	2.2		
7.5	217	113.94	2.6			31	52	44.90	2.3		
8.0	201	105.83	2.8			35	46	39.25	2.7		
8.9	182	95.91	3.1			38	44	36.79	2.8		
9.9	164	86.11	3.4			43	39	32.47	3.2		
11	141	74.17	4.0			48	35	28.78	3.5		
12	133	69.75	4.3			49	34	28.37	3.6		
7.0	232	199.81	2.4	R 67 RF67	4	53	31	26.09	3.9		
7.6	214	184.07	2.6			57	29	24.47	4.2		
8.8	184	158.14	3.1			62	26	22.32	4.6		
10	160	137.67	3.5			72	23	19.35	5.3		
11	150	128.97	3.8			77	21	18.08	5.7		
12	132	113.94	4.3			89	19	15.63	6.6		
13	123	105.83	4.6			105	16	13.28	7.8		
4.5	355	186.89	1.19	R 57 RF57	6	37	45	23.13	1.78	R 17 RF17	6
4.9	327	172.17	1.29			40	41	21.22	1.94		
5.7	281	147.92	1.50			47	35	18.06	2.28		
6.6	245	128.77	1.73			19	87	74.84	0.92	R 17 RF17	4
7.0	229	120.63	1.84	R 57 RF57	4	22	75	64.52	1.07		
7.4	217	186.89	1.95			23	70	60.14	1.14		
8.1	200	172.17	2.1			26	61	52.57	1.31		
9.4	172	147.92	2.5			28	57	49.28	1.39		
11	150	128.77	2.8			32	51	43.49	1.58		
12	140	120.63	3.0			34	47	40.49	1.70		
13	124	106.58	3.4			39	41	35.40	1.94		
14	115	98.99	3.7			42	39	33.18	2.07		
15	104	89.71	4.1			47	34	29.28	2.3		
7.9	206	176.88	1.37	R 47 RF47	4	54	30	25.96	2.6		
8.5	189	162.94	1.49			60	27	23.13	2.9		
9.9	163	139.99	1.73			63	26	22.06	3.1		
11	142	121.87	1.99			66	25	21.22	3.2		
12	133	114.17	2.1			77	21	18.06	3.7		
14	117	100.86	2.4			89	18	15.57	4.3		
15	109	93.68	2.6			96	17	14.52	4.6		
16	99	84.90	2.9			110	15	12.69	5.3		
18	89	76.23	3.2	R 37 RF37	6	117	14	11.89	5.7		
6.9	235	123.66	0.80			132	12	10.5	5.9		
8.1	200	105.28	0.94			149	11	9.31	6.1		
9.4	173	90.77	1.09			176	10	7.91	6.2		
10	161	84.61	1.17			184	9	7.55	6.5		
10	157	134.82	1.20	R 37 RF37	4	197	8	7.04	7.0		
11	144	123.66	1.31			226	7.5	6.15	7.2		
13	122	105.28	1.54			241	7	5.76	7.3		
15	106	90.77	1.78			273	6	5.09	7.9		
16	98	84.61	1.91			308	5	4.51	8.4		
19	86	73.96	2.2			363	4.5	3.83	10		
20	81	69.33	2.3			140	12	6.07	3.4	RX 67 RXF67	6
23	71	61.18	2.6			164	10	5.18	6.9		
25	65	55.76	2.9			188	9.0	4.53	8.6		
29	56	48.08	3.4			198	8.5	4.30	8.8		

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p
0.18kW						0.25kW					
229	7.4	6.07	5.5			0.69	3082	2016	0.92		
268	6.3	5.18	11			0.76	2787	1823	1.01		
307	5.5	4.53	14			0.80	2649	1733	1.06		
323	5.2	4.30	14			0.86	2481	1623	1.14		
369	4.6	3.77	18	RX 67	4	0.88	2420	1583	1.17	R 97R57	4
434	3.9	3.20	24	RXF 67	4	1.0	2134	1396	1.32	RF97R57	4
481	3.5	2.89	28			1.1	1877	1228	1.50		
547	3.1	2.54	36			1.3	1633	1068	1.73		
579	2.9	2.40	40			1.5	1432	937	1.97		
681	2.5	2.04	51			1.7	1260	824	2.2		
						1.9	1127	737	2.5		
						2.2	965	631	2.9		
155	11	5.50	3.36			1.2	1750	1145	0.83		
168	10	5.07	3.37	RX 57	6	1.3	1585	1037	0.92		
195	8.6	4.35	7.4	RXF 57	6	1.5	1423	931	1.02		
224	7.5	3.79	8.5			1.6	1350	883	1.08		
253	6.7	5.50	5.50			1.7	1226	802	1.19	R 87R57	4
274	6.1	5.07	5.51			1.8	1183	774	1.23	RF87R57	4
320	5.3	4.35	12			2.0	1044	683	1.40		
367	4.6	3.79	14			2.3	916	599	1.59		
392	4.3	3.55	15	RX 57	4	2.6	803	525	1.82		
443	3.8	3.14	16	RXF 57	4	3.1	694	454	2.1		
478	3.5	2.91	18			5.2	408	267	3.6		
527	3.2	2.64	20			2.4	873	571	0.88		
586	2.9	2.37	23			2.5	836	547	0.92		
681	2.5	2.04	26			2.9	729	477	1.06		
724	2.3	1.92	28			3.3	651	426	1.18	R 77R37	4
842	2.0	1.65	32			3.8	556	364	1.39	RF77R37	4
426	4	3.26	3.80	RX 37	4	4.5	477	312	1.62		
527	3	2.64	4.69	RXF 37	4	4.6	474	310	1.63		
0.25kW						5.6	379	248	2.03		
0.14	14894	9743	0.82			6.3	335	219	2.3		
0.16	12907	8443	0.95			3.6	593	388	0.95		
0.19	11170	7307	1.09			3.9	549	359	1.03		
0.22	9855	6447	1.24	R 147R77	4	4.1	514	336	1.10		
0.25	8512	5568	1.44	RF147R77	4	4.5	474	310	1.19		
0.29	7361	4815	1.66			4.8	439	287	1.29		
0.32	6612	4325	1.85			5.3	404	264	1.40		
0.38	5609	3669	2.18			5.5	390	255	1.45	R 67R37	4
0.43	4935	3228	2.48			5.9	359	235	1.57	RF67R37	4
0.49	4331	2833	2.82			6.1	350	229	1.61		
0.24	8918	5834	0.84			6.9	307	201	1.84		
0.28	7645	5001	0.98			7.1	298	195	1.89		
0.30	7199	4709	1.04			7.7	277	181	2.0		
0.32	6671	4364	1.13			8.1	263	172	2.15		
0.35	6142	4018	1.22			9.0	235	154	2.40		
0.37	6005	3928	1.25	R 137R77	4	4.3	495	324	0.85		
0.40	5372	3514	1.40	RF137R77	4	4.4	488	319	0.87		
0.42	5103	3338	1.47			4.8	443	290	0.95		
0.47	4478	2929	1.68			5.2	408	267	1.04		
0.52	4063	2658	1.85			5.3	401	262	1.06	R 57R37	4
0.58	3687	2412	2.0			5.7	376	246	1.12	RF57R37	4
0.67	3169	2073	2.4			5.8	368	241	1.15		
0.76	2811	1839	2.7			6.3	336	220	1.26		
0.99	2136	1397	3.5			6.5	329	215	1.29		
1.1	1874	1226	4.0			7.6	280	183	1.51		
0.46	4609	3015	0.88			8.6	246	161	1.72		
0.71	3013	1971	1.34			10	211	138	2.0		
0.77	2772	1813	1.46			6.1	349	228	0.81		
0.88	2426	1587	1.67	R 107R77	4	7.1	298	195	0.95	R 47R37	4
1.0	2123	1389	1.90	RF107R77	4	7.6	278	182	1.01	RF47R37	4
1.1	1859	1216	2.2			9.0	235	154	1.20		
1.5	1417	927	2.9								
1.7	1241	812	3.3								

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p
0.25kW						0.25kW					
8.9	238	156	0.79	R 37R17 RF37R17	4	7.4	308	186.89	1.37	R 57 RF57	4
9.3	229	150	0.82			8.1	284	172.17	1.49		
10	206	135	0.91			9.4	244	147.92	1.73		
11	194	127	0.97			11	212	128.77	1.99		
12	168	110	1.12			12	199	120.63	2.1		
13	159	104	1.18			13	176	106.58	2.4		
14	144	94	1.31			14	163	98.99	2.6		
15	138	90	1.37			15	148	89.71	2.9		
2.2	1029	289.60	2.7	R 97 RF97	8	17	133	80.55	3.2	R 47 RF47	4
2.5	913	256.89	3.1			20	114	69.23	3.7		
2.7	856	240.83	3.3			7.9	292	176.88	0.97		
3.0	767	215.94	3.7			8.5	269	162.94	1.05		
2.6	876	246.54	1.66	R 87 RF87	8	9.9	231	139.99	1.22		
3.0	769	216.54	1.89			11	201	121.87	1.40		
3.1	731	205.71	1.99			12	188	114.17	1.50		
3.5	646	181.77	2.3			14	166	100.86	1.70		
3.9	592	166.59	1.30	R 77 RF77	8	15	154	93.68	1.83		
4.4	518	145.67	1.49			16	140	84.90	2.0		
4.7	492	138.39	1.57			18	126	76.23	2.2		
5.3	431	121.42	1.79			20	113	68.54	2.5		
4.4	526	195.24	1.46	R 77 RF77	6	22	106	64.21	2.7		
5.1	449	166.59	1.72			25	94	56.73	3.0		
5.8	393	145.67	1.96			26	87	52.69	3.2		
7.1	322	195.24	2.4	R 77 RF77	4	29	79	47.75	3.6		
8.3	275	166.59	2.8			10	222	134.82	0.85	R 37 RF37	4
9.5	240	145.67	3.2			11	204	123.66	0.92		
10	228	138.39	3.4			13	174	105.28	1.08		
11	200	121.42	3.8			15	150	90.77	1.26		
4.1	562	158.14	1.00	R 67 RF67	8	16	140	84.61	1.35		
4.7	489	137.67	1.15			19	122	73.96	1.54		
5.0	458	128.97	1.23			20	114	69.33	1.64		
5.7	405	113.94	1.39			23	101	61.18	1.86		
4.3	539	199.81	1.05			25	92	55.76	2.0		
4.6	496	184.07	1.14	R 67 RF67	6	29	79	48.08	2.4		
5.4	426	158.14	1.32			31	74	44.81	2.5		
6.2	371	137.67	1.52			35	65	39.17	2.9		
6.6	348	128.97	1.62			38	61	36.72	3.1		
7.5	307	113.94	1.84			43	53	32.40	3.5		
8.0	285	105.83	1.98			16	140	84.78	0.87	R 27 RF27	4
7.0	329	199.81	1.71	R 67 RF67	4	19	122	74.11	1.00		
7.6	304	184.07	1.86			20	115	69.47	1.07		
8.8	261	158.14	2.2			23	101	61.30	1.21		
10	227	137.67	2.5			25	92	55.87	1.33		
11	213	128.97	2.7			29	79	48.17	1.54		
12	188	113.94	3.0			31	74	44.90	1.65		
13	175	105.83	3.2			35	65	39.25	1.89		
14	158	95.91	3.6			38	61	36.79	2.0		
16	142	86.11	4.0			43	54	32.47	2.3		
4.5	504	186.89	0.84	R 57 RF57	6	48	48	28.78	2.5		
4.9	464	172.17	0.91			49	47	28.37	2.6		
5.7	399	147.92	1.06			53	43	26.09	2.8		
6.6	347	128.77	1.22			57	40	24.47	3.0		
7.0	325	120.63	1.30			62	37	22.32	3.3		
8.0	287	106.58	1.47			72	32	19.35	3.8		
8.6	267	98.99	1.58			77	30	18.08	4.1		
						89	26	15.63	4.7		
						105	22	13.28	5.6		
						117	20	11.86	6.2		
						137	17	10.13	6.9		
						148	16	9.41	7.4		
						170	14	8.16	8.1		
						182	13	7.63	8.4		
						211	11	6.59	9.2		
						248	9.0	5.60	10		
						278	8.2	5.00	11		
						326	7.5	4.27	12		
						348	7.0	4.00	12		
						412	6.0	3.37	13		

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p
0.25kW						0.37kW					
26	87	52.57	0.92			0.19	16532	7307	0.80		
28	81	49.28	0.98			0.22	14586	6447	0.84		
32	72	43.49	1.11			0.25	12597	5568	0.97		
34	67	40.49	1.20			0.29	10894	4815	1.12	R 147R77	4
39	58	35.40	1.37			0.32	9785	4325	1.25	RF147R77	4
42	55	33.18	1.46			0.38	8301	3669	1.47		
47	48	29.28	1.65			0.43	7303	3228	1.67		
54	43	25.96	1.87			0.49	6410	2833	1.91		
60	38	23.13	2.1								
63	36	22.06	2.2			0.32	9873	4364	0.76		
66	35	21.22	2.3			0.35	8887	3928	0.85		
77	30	18.06	2.7	R 17	4	0.40	7950	3514	0.95		
89	26	15.57	3.1	RF 17	4	0.42	7552	3338	1.00		
96	24	14.52	3.3			0.47	6627	2929	1.13		
110	21	12.69	3.8			0.52	6014	2658	1.25		
117	20	11.89	4.1			0.56	5620	2484	1.34	R 137R77	4
132	17	10.5	4.2			0.58	5457	2412	1.38	RF137R77	4
149	15	9.31	4.4			0.62	5072	2242	1.48		
176	13	7.91	4.5			0.67	4690	2073	1.60		
184	12	7.55	4.7			0.76	4161	1839	1.81		
197	11	7.04	5.0			0.99	3161	1397	2.4		
226	10	6.15	5.2			1.1	2774	1226	2.7		
241	9	5.76	5.2			1.3	2466	1090	3.0		
273	8	5.09	5.7			1.5	2152	951	3.5		
308	7	4.51	6.1								
363	6	3.83	6.7			0.68	4618	2041	0.88		
140	16	6.07	2.5			0.71	4459	1971	0.91		
164	14	5.18	4.9	RX 67	6	0.77	4102	1813	0.99		
188	13	4.53	6.2	RXF 67	6	0.83	3785	1673	1.07		
198	12	4.30	6.4			0.88	3591	1587	1.13	R 107R77	4
						0.91	3464	1531	1.17	RF107R77	4
229	10	6.07	4.0			1.0	3145	1390	1.29		
268	9	5.18	8.1			1.1	2751	1216	1.47		
307	8	4.53	10			1.2	2701	1194	1.50		
323	7	4.30	10			1.3	2360	1043	1.71		
369	6	3.77	13	RX 67	4	1.5	2097	927	1.93		
434	5.5	3.20	17	RXF 67	4	1.7	1837	812	2.2		
481	5	2.89	20								
547	4.5	2.54	26			0.97	3244	1434	0.87		
579	4	2.40	29			1.0	3158	1396	0.89		
681	3	2.04	37			1.1	2778	1228	1.02		
						1.2	2731	1207	1.03		
155	15	5.50	2.4			1.3	2453	1084	1.15		
168	14	5.07	2.4	RX 57	6	1.4	2416	1068	1.17	R 97R57	4
195	12	4.35	5.3	RXF 57	6	1.5	2120	937	1.33	RF97R57	4
224	10	3.79	6.2			1.7	1864	824	1.51		
						1.9	1667	737	1.69		
253	9.3	5.50	4.0			2.2	1428	631	1.98		
274	8.5	5.07	4.0			3.2	973	430	2.9		
320	7.3	4.35	9.0			3.7	857	379	3.3		
367	6.4	3.79	10			4.1	760	336	3.7		
392	6.0	3.55	11								
443	5.3	3.14	12	RX 57	4						
478	4.9	2.91	13	RXF 57	4	1.7	1814	802	0.80		
527	4.4	2.64	15			1.8	1751	774	0.83		
586	4.0	2.37	16			1.9	1706	754	0.85		
681	3.4	2.04	19			2.0	1545	683	0.94		
724	3.2	1.92	20			2.1	1468	649	0.99		
842	2.8	1.65	23			2.3	1355	599	1.08		
						2.5	1217	538	1.20	R 87R57	4
370	6	3.76	2.37			2.6	1188	525	1.23	RF87R57	4
426	5.5	3.26	2.73			2.9	1068	472	1.36		
456	5	3.05	2.92			3.1	1027	454	1.42		
527	4.5	2.64	3.38	RX 37	4	3.5	905	400	1.61		
621	4	2.24	3.98	RXF 37	4	3.9	817	361	1.78		
695	3.5	2.00	4.46			5.2	604	267	2.4		
813	3	1.71	5.21			5.9	532	235	2.7		
869	2.5	1.60	5.57								

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p
0.37kW						0.37kW					
3.3	964	426	0.80	R 77R37 RF 77R37	4 4	6.6	503	128.77	0.84	R 57 RF 57	6 6
3.8	824	364	0.94			7.0	471	120.63	0.90		
4.3	740	327	1.04			8.0	416	106.58	1.02		
4.5	701	310	1.10			8.6	387	98.99	1.09		
5.6	561	248	1.37			7.4	447	186.89	0.95		
6.3	495	219	1.56			8.1	411	172.17	1.03	R 57 RF 57	4 4
7.4	425	188	1.81			9.4	353	147.92	1.20		
8.6	367	162	2.1			11	308	128.77	1.37		
9.8	321	142	2.4			12	288	120.63	1.47		
4.8	649	287	0.87	R 67R37 RF 67R37	4 4	13	255	106.58	1.66		
5.5	577	255	0.98			14	237	98.99	1.79		
6.1	518	229	1.09			15	214	89.71	1.97		
7.1	441	195	1.28			17	192	80.55	2.2		
2.5	1323	256.89	2.1	R 97 RF 97	8 8	20	165	69.23	2.6	R 47 RF 47	4 4
2.7	1240	240.83	2.3			21	155	64.85	2.7		
3.0	1112	215.94	2.5			24	137	57.29	3.1		
3.5	958	185.97	2.9			26	127	53.22	3.3		
2.9	1132	289.60	2.5	R 97 RF 97	6 6	29	115	48.23	3.7		
3.3	1004	256.89	2.8			9.9	335	139.99	0.84		
3.5	941	240.83	3.0			11	291	121.87	0.97		
3.9	844	215.94	3.3			12	273	114.17	1.03		
3.0	1115	216.54	1.31	R 87 RF 87	8 8	14	241	100.86	1.17		
3.1	1059	205.71	1.38			15	224	93.68	1.26		
3.5	936	181.77	1.6			16	203	84.90	1.39		
3.4	963	246.54	1.51			18	182	76.23	1.55		
3.9	846	216.54	1.72	R 87 RF 87	6 6	20	164	68.54	1.72		
4.1	804	205.71	1.81			22	153	64.21	1.84		
4.7	710	181.77	2.1			25	136	56.73	2.1		
5.5	607	155.34	2.4			26	126	52.69	2.2		
6.0	556	142.41	2.6			29	114	47.75	2.5		
4.4	750	145.67	1.03	R 77 RF 77	8 8	32	102	42.87	2.8		
4.7	713	138.39	1.08			38	88	36.93	2.8		
5.3	625	121.42	1.23			40	83	34.73	2.8		
5.1	651	166.59	1.18	R 77 RF 77	6 6	41	81	33.79	3.2	R 37 RF 37	4 4
5.8	569	145.67	1.35			45	74	31.12	3.4		
6.1	541	138.39	1.43			52	64	26.74	4.4		
7.1	467	195.24	1.65	R 77 RF 77	4 4	60	56	23.28	5.1		
8.3	398	166.59	1.94			64	52	21.81	5.4		
9.5	348	145.67	2.2			15	217	90.77	0.87		
10	331	138.39	2.3			16	202	84.61	0.93		
11	290	121.42	2.7			19	177	73.96	1.06		
13	246	102.99	3.1			20	166	69.33	1.13		
15	222	92.97	3.47			23	146	61.18	1.29		
5.4	618	158.14	0.91	R 67 RF 67	6 6	25	133	55.76	1.41		
6.2	538	137.67	1.05			29	115	48.08	1.64		
6.6	504	128.97	1.12			31	107	44.81	1.76		
7.5	445	113.94	1.27			35	94	39.17	2.0		
7.0	477	199.81	1.18	R 67 RF 67	4 4	38	88	36.72	2.1		
7.6	440	184.07	1.28			43	77	32.40	2.4		
8.8	378	158.14	1.49			48	69	28.73	2.7		
10	329	137.67	1.71			49	68	28.32	2.8		
11	308	128.97	1.83			53	62	26.03	2.8		
12	272	113.94	2.1			57	58	24.42	3.2		
13	253	105.83	2.2			62	53	22.27	3.5		
14	229	95.91	2.5			72	46	19.31	4.1		
16	206	86.11	2.7			77	43	18.05	4.4		
19	177	74.17	3.2			89	38	15.60	4.9		
20	167	69.75	3.4			105	32	13.25	5.5		
23	146	61.26	3.9			117	29	11.83	6.0		
24	136	56.89	4.1								

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p		
0.37kW						0.37kW							
23	146	61.30	0.83	R 27 RF27	4	253	13.7	5.50	2.7	RX 57 RXF57	4		
25	134	55.87	0.92			274	12.6	5.07	2.7				
29	115	48.17	1.06			320	10.8	4.35	5.9				
31	107	44.90	1.14			367	9.4	3.79	6.9				
35	94	39.25	1.30			392	8.8	3.55	7.3				
38	88	36.79	1.39			443	7.8	3.14	7.8				
43	78	32.47	1.57			478	7.2	2.91	8.7				
48	69	28.78	1.78			527	6.6	2.64	9.9	RX 37 RXF37	4		
49	68	28.37	1.80			586	5.9	2.37	11				
53	62	26.09	1.96			681	5.1	2.04	13				
57	58	24.47	2.1			724	4.8	1.92	14				
62	53	22.32	2.3			842	4.1	1.65	16				
72	46	19.35	2.6										
77	43	18.08	2.8										
89	37	15.63	3.3										
105	32	13.28	3.9										
39	85	35.40	0.94	R 17 RF17	4	426	9	3.26	1.85	RX 37 RXF37	4		
42	79	33.18	1.01			456	8	3.05	1.97				
47	70	29.28	1.14			527	7	2.64	2.28				
54	62	25.96	1.29			621	6	2.24	2.69				
60	55	23.13	1.45			695	5	2.00	3.01				
63	53	22.06	1.52			813	4.5	1.71	3.52				
66	51	21.22	1.58			869	4	1.60	3.76				
77	43	18.06	1.85			0.55kW							
89	37	15.57	2.1			0.23	20411	6069	0.83	R 167R97 RF167R97	4		
96	35	14.52	2.3			0.26	18157	5399	0.93				
110	30	12.69	2.6			0.30	15837	4709	1.07				
117	28	11.89	2.8			0.33	14065	4182	1.20				
132	25	10.50	2.9			0.29	16193	4815	0.75	R 147R77 RF147R77	4		
149	22	9.31	3.0			0.32	14545	4325	0.84				
176	19	7.91	3.1			0.38	12339	3669	0.99				
184	18	7.55	3.3	0.43	10856	3228	1.13						
197	17	7.04	3.5	0.49	9528	2833	1.28						
226	15	6.15	3.6	0.54	8593	2555	1.42						
241	14	5.76	3.6	0.63	7436	2211	1.64						
273	12	5.09	3.9	0.71	6561	1951	1.86						
308	11	4.51	4.2	0.82	5734	1705	2.1						
363	9	3.83	4.6	0.90	5166	1536	2.4						
				1.05	4470	1329	2.7						
				1.19	3921	1166	3.1						
164	21	5.18	3.3	RX 67 RXF67	6	0.52	8939	2658	0.84	R 137R77 RF137R77	4		
188	19	4.53	4.2			0.56	8354	2484	0.90				
198	18	4.30	4.3			0.58	8112	2412	0.93				
225	15	3.77	5.3			0.67	6972	2073	1.08				
						0.76	6185	1839	1.22				
229	15	6.07	2.7	RX 67 RXF67	4	0.87	5374	1598	1.40			R 107R77 RF107R77	4
268	13	5.18	5.5			0.99	4698	1397	1.60				
307	12	4.53	6.8			1.1	4123	1226	1.82				
323	11	4.30	7.0			1.3	3666	1090	2.1				
369	9	3.77	8.7			1.5	3198	951	2.4				
434	8	3.20	12			1.7	2795	831	2.7				
481	7	2.89	14			1.0	4675	1390	0.86				
547	6.3	2.54	18			1.1	4090	1216	0.99				
579	6.0	2.40	19			1.2	4016	1194	1.01				
681	5.1	2.04	25			1.3	3683	1095	1.10				
195	17.7	4.35	3.6	RX 57 RXF57	6	1.4	3508	1043	1.15	R 107R77 RF107R77	4		
224	15.4	3.79	4.2			1.5	3118	927	1.30				
239	14.5	3.55	4.5			1.6	2986	888	1.35				
						1.7	2731	812	1.48				
						1.8	2647	787	1.53				
						2.0	2327	692	1.74				
						2.3	2035	605	1.99				

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
0.55kW						0.55kW					
1.5	3151	937	0.89	R 97R57 RF97R57	4 4	8.8	562	158.14	1.00	R 67 RF67	4 4
1.7	2771	824	1.02			10	489	137.67	1.15		
1.9	2479	737	1.14			11	458	128.97	1.23		
2.2	2122	631	1.33			12	405	113.94	1.39		
2.5	1883	560	1.50			13	376	105.83	1.50		
2.9	1628	484	1.73			14	341	95.91	1.66		
3.2	1446	430	1.95			16	306	86.11	1.84		
3.7	1275	379	2.2			19	263	74.17	2.1		
4.1	1130	336	2.5			20	248	69.75	2.3		
4.7	995	296	2.8			23	218	61.26	2.6		
5.6	837	249	3.4			24	202	56.89	2.8		
2.6	1766	525	0.83	R 87R57 RF87R57	4 4	12	428	120.63	0.99	R 57 RF57	4 4
2.9	1587	472	0.92			13	379	106.58	1.12		
3.1	1527	454	0.95			14	352	98.99	1.20		
3.5	1345	400	1.08			15	319	89.71	1.33		
3.6	1332	396	1.09			17	286	80.55	1.48		
3.9	1214	361	1.20			20	246	69.23	1.72		
4.0	1180	351	1.23	R 77R37 RF77R37	4 4	21	230	64.85	1.84		
4.6	1026	305	1.42			24	203	57.29	2.1		
5.1	925	275	0.83			26	189	53.22	2.2		
5.9	794	236	0.97			29	171	48.23	2.5		
6.3	743	221	1.04			32	154	43.30	2.8		
7.8	599	178	1.29			37	132	37.30	3.2		
2.6	1893	256.89	1.50	R 97 RF97	8 8	40	125	35.07	3.4		
2.8	1775	240.83	1.59			53	93	26.31	4.5		
3.1	1591	215.94	1.77			56	89	24.99	4.8		
2.9	1682	289.60	1.68	R 97 RF97	6 6	63	78	21.93	5.4		
3.3	1492	256.89	1.90			75	66	18.60	6.4		
3.5	1399	240.83	2.0			15	333	93.68	0.85	R 47 RF47	4 4
3.9	1254	215.94	2.2			16	302	84.90	0.94		
4.8	1029	289.60	2.7	R 97 RF97	4 4	18	271	76.23	1.04		
5.4	912	256.89	3.1			20	243	68.54	1.16		
5.8	855	240.83	3.3			22	228	64.21	1.24		
6.4	767	215.94	3.7			25	202	56.73	1.40		
3.6	1375	246.54	1.06	R 87 RF87	6 6	26	187	52.69	1.51		
4.1	1208	216.54	1.21			29	170	47.75	1.66		
4.3	1148	205.71	1.27			32	152	42.87	1.85		
4.9	1014	181.77	1.44			38	131	36.93	2.1		
5.7	867	155.34	1.68			40	123	34.73	2.3		
5.6	876	246.54	1.66	R 87 RF87	4 4	47	106	29.88	2.7		
6.4	769	216.54	1.89			52	95	26.74	3.0		
6.8	731	205.71	2.0			60	83	23.28	3.4		
7.6	646	181.77	2.3			64	77	21.81	3.6		
8.9	552	155.34	2.6			23	217	61.18	0.87	R 37 RF37	4 4
9.8	506	142.41	2.9			25	198	55.76	0.95		
11	444	124.97	3.3			29	171	48.08	1.10		
12	421	118.43	3.5			31	159	44.81	1.18		
13	368	103.65	4.0			35	139	39.17	1.35		
8.3	592	166.59	1.30	R 77 RF77	4 4	38	130	36.72	1.44		
9.5	517	145.67	1.49			43	115	32.40	1.63		
10	492	138.39	1.57			48	102	28.73	1.84		
11	431	121.42	1.79			57	87	24.42	2.2		
13	366	102.99	2.1			62	79	22.27	2.4		
15	330	92.97	2.3			72	69	19.31	2.7		
17	291	81.80	2.7			77	64	18.05	2.9		
18	274	77.24	2.8			89	55	15.60	3.4		
21	234	65.77	3.3			105	47	13.25	4.0		
						117	42	11.83	4.5		

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p		
0.55kW						0.55kW							
35	139	39.25	0.88	R 27 RF27	4	320	16	4.35	4.0	RX 57 RXF57	4		
38	131	36.79	0.94			367	14	3.79	4.6				
43	115	32.47	1.06			392	13	3.55	4.9				
48	102	28.78	1.20			443	12	3.14	5.3				
57	87	24.47	1.41			478	11	2.91	5.8				
62	79	22.32	1.54			527	10	2.64	6.6				
72	69	19.35	1.78			586	9	2.37	7.4				
77	64	18.08	1.90			681	8	2.04	8.6				
89	56	15.63	2.2			724	7	1.92	9.1				
105	47	13.28	2.6			842	6	1.65	11				
117	42	11.86	2.9			939	5	1.48	12				
137	36	10.13	3.2			1069	4.5	1.30	12				
148	33	9.41	3.4										
170	29	8.16	3.8										
182	27	7.63	3.9										
211	23	6.59	4.3										
248	20	5.60	4.7										
278	18	5.00	5.0										
326	15	4.27	5.4										
348	14	4.00	5.6										
412	12	3.37	6.2										
						0.75kW							
77	64	18.06	1.25	R 17 RF17	4	0.30	21596	4709	0.8	R 167R97 RF167R97	4		
89	55	15.57	1.44			0.33	19179	4182	0.88				
96	52	14.52	1.55			0.52	12185	2657	1.39				
110	45	12.69	1.77			0.60	10699	2333	1.58				
117	42	11.89	1.89			0.67	9562	2085	1.77				
132	37	10.50	2.0			0.95	6677	1456	2.5				
149	33	9.31	2.0										
161	31	8.63	2.1			0.43	14804	3228	0.83	R 147R77 RF147R77	4		
176	28	7.91	2.2			0.49	12992	2833	0.94				
184	27	7.55	2.2			0.54	11717	2555	1.04				
197	25	7.04	2.3			0.63	10140	2211	1.21				
226	22	6.15	2.4			0.71	8947	1951	1.37				
241	20	5.76	2.6			0.82	7819	1705	1.56				
273	18	5.09	2.7			0.90	7044	1536	1.73				
308	16	4.51	2.8			1.0	6095	1329	2.0				
363	14	3.83	3.1			1.2	5347	1166	2.3				
171	30	5.18	2.3			RX 67 RXF67	6	0.67	9507	2073	0.79	R 137R77 RF137R77	4
195	26	4.53	2.9	0.7	8544			1863	0.88				
206	25	4.30	3.0	0.76	8434			1839	0.89				
235	22	3.77	3.7	0.87	7287			1589	1.03				
								0.9	7273	1586	1.03		
268	19	5.18	3.7	RX 67 RXF67	4	0.99	6407	1397	1.17	R 107R77 RF107R77	4		
307	17	4.53	4.6			1.0	6237	1360	1.21				
323	16	4.30	4.7			1.1	5632	1228	1.34				
369	14	3.77	5.9			1.2	5623	1226	1.34				
434	12	3.20	7.9			1.3	4999	1090	1.50				
481	11	2.89	9.3			1.5	4361	951	1.72				
547	10	2.54	12			1.7	3811	831	1.97				
579	9	2.40	13			1.9	3348	730	2.2				
681	8	2.04	17			1.3	5022	1095	0.80			R 97R57 RF97R57	4
747	7	1.86	17			1.4	4783	1043	0.85				
863	6	1.61	18			1.5	4251	927	0.95				
						1.6	4072	888	0.99				
203	25	4.35	2.5	RX 57 RXF57	6	1.7	3724	812	1.09				
234	22	3.79	2.9			1.8	3609	787	1.12				
249	21	3.55	3.1			3.9	1637	357	2.5				
282	18	3.14	3.3			4.4	1435	313	2.8				
304	17	2.91	3.7										
						2.2	2894	631	0.97				
						2.5	2568	560	1.10				
						2.9	2220	484	1.27				
						3.2	1972	430	1.43				
						3.7	1738	379	1.62				
						4.1	1541	336	1.83				
						4.7	1357	296	2.1				
						5.6	1142	249	2.5				

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p
0.75kW						0.75kW					
3.5	1816	396	0.80	R 87R57 RF87R57	4	13	516	106.58	0.82	R 57 RF57	4
3.9	1656	361	0.91			14	479	98.99	0.88		
4.0	1610	351	1.04			15	435	89.71	0.97		
4.6	1399	305	1.19			17	390	80.55	1.08		
4.7	1376	300	1.35			20	335	69.23	1.26		
5.2	1224	267	1.70			21	314	64.85	1.35		
5.4	1174	256	2.0			24	277	57.29	1.52		
5.9	1078	235	2.4			26	258	53.22	1.64		
2.8	2445	245.50	1.65	R 107 RF107	8	29	234	48.23	1.81		
3.0	2259	226.11	1.81		8	32	210	43.30	2.0		
3.4	1995	200.87	2.0		8	37	181	37.30	2.3		
3.1	2138	215.94	1.32	R 97 RF97	8	40	170	35.07	2.5		
3.7	1841	185.97	1.53		8	46	146	30.18	2.9		
4.0	1674	169.06	1.68		8	52	131	26.97	3.2		
3.6	1901	256.89	1.49	R 97 RF97	6	53	130	26.31	3.3		
3.8	1782	240.83	1.58		6	56	124	24.99	3.4		
4.2	1598	215.94	1.76		6	63	103	21.93	3.9		
4.8	1403	289.60	2.0	R 97 RF97	4	75	92	18.60	4.6		
5.4	1244	256.89	2.3		4	20	332	68.54	0.85	R 47 RF47	4
5.8	1167	240.83	2.4		4	22	311	64.21	0.91		
6.4	1046	215.94	2.7		4	25	275	56.73	1.03		
7.5	901	185.97	3.1		4	26	255	52.69	1.10		
8.2	819	169.06	3.4		4	29	231	47.75	1.22		
4.2	1602	216.54	0.91	R 87 RF87	6	32	208	42.87	1.36		
4.4	1522	205.71	0.96		6	38	179	36.93	1.58		
5.0	1345	181.77	1.08		6	40	168	34.73	1.68		
5.9	1149	155.34	1.27		6	47	145	29.88	1.95		
6.4	1054	142.41	1.38		6	52	130	26.74	2.2		
5.6	1194	246.54	1.22	R 87 RF87	4	53	129	26.70	2.2		
6.4	1049	216.54	1.39		4	59	114	23.59	2.5		
6.8	996	205.71	1.46		4	60	113	23.28	2.5		
7.6	880	181.77	1.65		4	64	106	21.81	2.7		
8.9	752	155.34	1.94		4	72	93	19.27	3.0		
9.8	690	142.41	2.1		4	78	87	17.89	3.1		
11	605	124.97	2.4		4	86	79	16.22	3.3		
12	574	118.43	2.5		4	29	233	48.08	0.81	R 37 RF37	4
13	502	103.65	2.9		4	31	217	44.81	0.87		
15	452	93.38	3.2		4	35	190	39.17	0.99		
8.3	807	166.59	0.96	R 77 RF77	4	38	178	36.72	1.06		
9.5	706	145.67	1.09		4	43	157	32.40	1.20		
10	670	138.39	1.15		4	48	139	28.73	1.35		
11	588	121.42	1.31		4	57	118	24.42	1.59		
13	499	102.99	1.55		4	62	110	22.27	1.71		
15	450	92.97	1.71		4	72	96	19.31	1.97		
17	396	81.80	1.95		4	77	89	18.05	2.1		
18	375	77.24	2.1		4	89	77	15.60	2.4		
21	319	65.77	2.4		4	105	66	13.25	2.7		
25	273	56.38	2.8		4	117	59	11.83	2.9		
27	247	50.90	3.1		4	137	50	10.11	3.2		
31	217	44.78	3.6		4	147	47	9.47	3.4		
33	205	42.29	3.8		4	48	139	28.78	0.88	R 27 RF27	4
11	625	128.97	0.90	R 67 RF67	4	57	119	24.47	1.03		
12	552	113.94	1.02		4	62	110	22.32	1.11		
13	513	105.83	1.10		4	72	96	19.35	1.28		
14	465	95.91	1.21		4	77	89	18.08	1.37		
16	417	86.11	1.35		4	89	77	15.63	1.58		
19	359	74.17	1.57		4	105	66	13.28	1.86		
20	338	69.75	1.67		4	117	59	11.86	2.1		
23	297	61.26	1.90		4	137	50	10.13	2.3		
24	276	56.89	2.0		4	148	47	9.41	2.5		
27	250	51.56	2.3		4	170	40	8.16	2.7		
30	224	46.29	2.5		4	182	38	7.63	2.8		
						211	33	6.59	3.1		
						248	28	5.60	3.4		
						278	25	5.00	3.6		

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p
0.75kW						1.1kW					
77	89	18.06	0.89	R 17 RF 17	4	0.53	17744	2657	0.95	R 167R97 RF 167R97	4
89	77	15.57	1.04			0.60	15580	2333	1.09		
96	72	14.52	1.11			0.67	13924	2085	1.22		
110	63	12.69	1.27			0.75	12535	1877	1.35		
117	59	11.89	1.36			0.84	11153	1670	1.52		
132	52	10.50	1.41			0.96	9723	1456	1.74		
149	46	9.31	1.47			1.1	8655	1296	2.0	R 147R77 RF 147R77	4
176	39	7.91	1.48			1.2	7593	1137	2.2		
184	37	7.55	1.57			0.63	14765	2211	0.83		
197	35	7.04	1.67			0.72	13029	1951	0.94		
226	30	6.15	1.73			0.82	11386	1705	1.07		
241	28	5.76	1.75			0.91	10258	1536	1.19		
273	25	5.09	1.90			1.1	8875	1329	1.38		
308	22	4.51	2.0			1.2	7787	1166	1.57		
363	19	3.83	2.2			1.4	6872	1029	1.78		
201	35	4.53	2.2	RX 67 RXF 67	6	1.6	5937	889	2.1		
212	33	4.30	2.3			1.8	5236	784	2.3		
241	29	3.77	2.8			2.0	4641	695	2.6		
284	25	3.20	3.8			1.0	9082	1360	0.83	R 137R77 RF 137R77	4
268	26	5.18	2.7	RX 67 RXF 67	4	1.1	8201	1228	0.92		
307	23	4.53	3.4			1.2	8187	1226	0.95		
323	22	4.30	3.5			1.3	7212	1080	1.04		
369	19	3.77	4.3			1.4	6812	1020	1.10		
434	16	3.20	5.8			1.5	6351	951	1.18		
481	15	2.89	6.8			1.6	5803	869	1.30		
547	13	2.54	8.6			1.7	5550	831	1.36		
579	12	2.40	9.5			1.9	4875	730	1.54		
681	10	2.04	12			2.2	4201	629	1.79		
747	9	1.86	13			2.6	3666	549	2.1		
863	8	1.61	13			2.9	3272	490	2.3		
240	29	3.79	2.2	RX 57 RXF 57	6	2.0	4621	692	0.87	R 107R77 RF 107R77	4
256	27	3.55	2.4			2.3	3994	598	1.01		
290	24	3.14	2.5			2.6	3539	530	1.14		
313	22	2.91	2.8			2.9	3199	479	1.26		
345	20	2.64	3.2			3.4	2711	406	1.49		
320	22	4.35	2.9	RX 57 RXF 57	4	3.9	2384	357	1.70		
367	19	3.79	3.4			4.5	2090	313	1.93	R 97R57 RF 97R57	4
392	18	3.55	3.6			5.1	1850	277	2.2		
443	16	3.14	3.9			5.7	1636	245	2.5		
478	15	2.91	4.3			3.3	2872	430	0.98		
527	13	2.64	4.9			3.7	2531	379	1.11		
586	12	2.37	5.4			4.2	2244	336	1.26		
681	11	2.04	6.3			4.7	1977	296	1.43	R 87R57 RF 87R57	4
724	10	1.92	6.7			5.6	1663	249	1.70		
842	9	1.65	7.8			6.0	1563	234	1.80		
939	8	1.48	8.6			6.7	1396	209	2.0		
1069	7	1.30	9.0			5.2	1783	267	0.82		
456	15	3.05	0.97	RX 37 RXF 37	4	5.5	1710	256	0.85		
527	13	2.64	1.13			6.0	1569	235	0.93		
621	11	2.24	1.33			6.1	1543	231	0.94		
695	10	2.00	1.49			6.7	1389	208	1.05		
813	9	1.71	1.74			7.2	1302	195	1.12		
869	8	1.60	1.86			2.8	3586	245.50	1.13	R 107 RF 107	8
						3.0	3283	226.11	1.23		
						3.4	2901	200.87	1.39		
						4.0	2461	167.29	1.64		

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p
1.1kW						1.1kW					
3.5	2788	256.89	1.02	R 97 RF97	6	20	488	69.23	0.87	R 57 RF57	4 4
3.8	2613	240.83	1.08		6	22	457	64.85	0.92		
4.2	2343	215.94	1.20		6	24	404	57.29	1.05		
4.9	2018	185.97	1.39		6	26	375	53.22	1.13		
5.4	1812	256.89	1.56	R 97 RF97	4 4	29	340	48.23	1.24		
5.8	1699	240.83	1.66			32	305	43.30	1.39		
6.5	1523	215.94	1.85			38	263	37.30	1.61		
7.5	1312	185.97	2.1			40	247	35.07	1.71		
8.3	1192	169.06	2.4			46	213	30.18	1.99		
9.3	1064	150.78	2.7			52	190	26.97	2.2		
11	894	126.75	3.2			53	186	26.31	2.3		
12	822	116.48	3.4			56	176	24.99	2.4		
6.5	1527	216.54	0.95	R 87 RF87	4 4	64	155	21.93	2.7	R 47 RF47	4 4
6.8	1451	205.71	1.00			75	131	18.60	3.2		
7.7	1282	181.77	1.14			83	118	16.79	3.6		
9.0	1096	155.34	1.33			29	337	47.75	0.84		
9.8	1004	142.41	1.45			33	302	42.87	0.93		
11	881	124.97	1.65			38	260	36.93	1.08		
12	835	118.43	1.74			40	245	34.73	1.15		
14	731	103.65	1.99			47	211	29.88	1.34		
15	659	93.38	2.2			52	188	26.70	1.50		
17	578	81.92	2.5			59	166	23.59	1.69		
19	510	72.37	2.9			60	164	23.28	1.72		
22	448	63.50	3.3			64	154	21.81	1.83		
23	424	60.18	3.4			73	136	19.27	2.0		
27	372	52.67	3.9			78	126	17.89	2.2		
12	856	121.42	0.90	R 77 RF77	4 4	86	114	16.22	2.3	R 37 RF37	4 4
14	726	102.99	1.06			96	103	14.56	2.4		
15	656	92.97	1.18			112	88	12.54	2.7		
17	577	81.80	1.34			119	83	11.79	2.8		
18	545	77.24	1.41			138	72	10.15	3.0		
21	464	65.77	1.66			154	64	9.07	3.2		
25	398	56.38	1.94			43	229	32.40	0.82		
28	359	50.90	2.1			49	203	28.73	0.93		
31	316	44.78	2.4			57	172	24.42	1.09		
33	298	42.29	2.6			73	139	19.31	1.35		
39	254	36.01	3.0			78	130	18.05	1.45		
43	231	32.72	3.3			90	112	15.60	1.67		
16	607	86.11	0.93	R 67 RF67	4 4	106	95	13.25	1.87	R 27 RF27	4 4
19	523	74.17	1.08			118	85	11.83	2.0		
20	492	69.75	1.15			138	73	10.11	2.2		
23	432	61.26	1.31			148	68	9.47	2.3		
25	401	56.89	1.41			176	57	7.97	2.6		
27	364	51.56	1.55			210	48	6.67	2.8		
30	326	46.29	1.73			247	41	5.67	3.3		
35	281	39.88	1.9			277	36	5.06	3.5		
37	265	37.50	2.0			72	139	19.35	0.88		
43	228	32.27	2.2			77	130	18.08	0.94		
49	203	28.83	2.4			90	113	15.63	1.09		
50	201	28.13	2.5			105	96	13.28	1.28		
52	192	26.72	2.6			118	85	11.86	1.42		
60	169	23.44	3.1			138	73	10.13	1.57		
70	143	19.89	3.9			172	59	8.16	1.86		
						183	55	7.63	1.92		
						212	47	6.59	2.1		
						250	40	5.60	2.3		
						280	36	5.00	2.5		
						328	31	4.27	2.7		
						350	29	4.00	2.8		
						415	24	3.37	3.1		

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p
1.1kW						1.5kW					
249	41	5.63	2.5	RX 77 RXF77	4	1.3	10038	1090	0.75	R 137R77 RF137R77	4
262	39	5.35	2.7		4	1.4	9393	1020	0.80		
296	35	4.73	3.3		4	1.5	8758	951	0.86		
201	51	4.53	1.50	RX 67 RXF67	6	1.6	8003	869	0.94		
212	49	4.30	1.55		6	1.7	7653	831	0.98		
241	43	3.77	1.92		6	1.9	6723	730	1.12		
309	33	4.53	2.3	RX 67 RXF67	4	2.0	6299	684	1.19		
326	32	4.30	2.4			2.2	5792	629	1.30		
371	28	3.77	2.9			2.4	5479	595	1.37		
438	24	3.20	4.0			2.6	5056	549	1.49		
484	21	2.89	4.7			2.9	4512	490	1.67		
551	19	2.54	5.9			3.3	3941	428	1.91		
583	18	2.40	6.6			3.7	3444	374	2.2		
686	15	2.04	8.4			4.4	2919	317	2.6		
753	14	1.86	8.7			2.6	4827	530	0.84	R 107R77 RF107R77	4
870	12	1.61	9.1			2.7	4644	510	0.87		
1000	10	1.40	9.5			2.9	4362	479	0.93		
240	43	3.79	1.5	RX 57 RXF57	6	3.0	4216	463	0.96		
256	40	3.55	1.6			3.4	3697	406	1.09		
290	36	3.14	1.7			3.9	3251	357	1.24		
313	33	2.91	1.9			4.5	2850	313	1.42		
345	30	2.64	2.2	RX 57 RXF57	4	4.2	3060	336	0.92	R 97R57 RF97R57	4
369	28	3.79	2.3			4.7	2696	296	1.05		
394	26	3.55	2.5			5.6	2268	249	1.24		
446	23	3.14	2.6			6.0	2131	234	1.32		
481	21	2.91	2.9			6.7	1903	209	1.48	R 107 RF107	8
530	19	2.64	3.3			3.1	4413	226.11	0.92		
591	17	2.37	3.7			3.5	3920	200.87	1.03		
686	15	2.04	4.3			4.1	3265	167.29	1.24		
729	14	1.92	4.6			4.4	3045	156.04	1.32	R 107 RF107	6
848	12	1.65	5.3			3.7	3593	245.50	1.12		
946	11	1.48	5.9			4.1	3309	226.11	1.22		
1077	10	1.30	6.2			4.6	2940	200.87	1.37		
700	15	2.00	1.02	RX 37 RXF37	4	5.5	2449	167.29	1.65		
819	13	1.71	1.19			5.8	2304	156.04	1.77	R 97 RF97	4
875	12	1.60	1.27			6.6	2041	139.47	1.98		
0.60	21246	2333	0.80	R 167R97 RF167R97	4	5.4	2417	256.89	1.14		
0.67	18987	2085	0.89			5.8	2316	240.83	1.22		
0.75	17093	1877	0.99			6.5	2077	215.94	1.36		
0.84	15208	1670	1.11			7.5	1789	185.97	1.58		
0.96	13259	1456	1.28			8.3	1626	169.06	1.73		
1.1	11802	1296	1.43			9.3	1450	150.78	1.94		
1.2	10354	1137	1.63			11	1219	126.75	2.3	R 87 RF87	4
1.4	9216	1012	1.84			12	1120	116.48	2.5		
3.2	3934	432	3.1	R 147R87 RF147R87	4	14	995	103.44	2.8		
3.8	3388	373	3.6			15	889	92.48	3.2		
0.82	15527	1705	0.8	R 147R77 RF147R77	4	7.7	1748	181.77	0.83		
0.91	13988	1536	0.87			9.0	1494	155.34	0.98		
1.1	12103	1329	1.01			9.8	1370	142.41	1.06		
1.2	10618	1166	1.15			11	1202	124.97	1.21		
1.4	9371	1029	1.30			12	1139	118.43	1.28		
1.6	8096	889	1.51			14	997	103.65	1.46		
1.8	7140	784	1.71			15	898	93.38	1.62		
2.0	6329	695	1.93			17	788	81.92	1.85		
2.3	5528	607	2.2			19	696	72.37	2.1		
2.6	4981	547	2.5			22	611	63.50	2.4		
						23	579	60.18	2.5		
						27	507	52.67	2.9		
						30	456	47.45	3.2		
						34	400	41.63	3.6		
						38	353	36.73	4.1		

输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p				
1.5kW						1.5kW									
15	894	92.97	0.86	R 77 RF77	4 4	73	186	19.31	1.01	R 37 RF37	4 4				
17	787	81.80	0.98			78	174	18.05	1.08						
18	743	77.24	1.04			90	150	15.60	1.25						
21	633	65.77	1.22			106	127	13.25	1.40						
25	542	56.38	1.42			118	114	11.83	1.51						
28	490	50.90	1.57			138	97	10.11	1.64						
31	431	44.78	1.79			148	91	9.47	1.72						
33	407	42.29	1.90			176	77	7.97	1.91						
39	346	36.01	2.2			210	64	6.67	2.1						
43	315	32.72	2.4			247	55	5.67	2.4						
49	273	28.35	2.8			277	49	5.06	2.6						
57	237	24.67	3.1			324	42	4.32	2.9						
60	225	23.37	3.4			346	39	4.05	2.9						
65	206	21.43	3.7			411	33	3.41	3.2						
74	181	18.80	4.1												
23	589	61.26	0.96	R 67 RF67	4 4	90	150	15.63	0.81	R 27 RF27	4 4				
25	547	56.89	1.03			105	128	13.28	0.96						
27	496	51.56	1.14			118	114	11.86	1.06						
30	445	46.29	1.27			138	97	10.13	1.18						
35	384	39.88	1.47			172	78	8.16	1.39						
37	361	37.50	1.56			183	73	7.63	1.43						
43	310	32.27	1.82			212	63	6.59	1.57						
49	277	28.83	2.0			250	54	5.60	1.73						
50	276	28.13	2.0			280	48	5.00	1.86						
52	262	26.72	2.1			328	41	4.27	1.99						
60	230	23.44	2.4			350	38	4.00	2.1						
70	195	19.89	2.9			415	32	3.37	2.3						
78	176	17.95	3.2												
26	523	53.22	0.8			R 57 RF57	4 4	249	54			5.63	1.91	RX 77 RXF77	4 4
29	474	48.23	0.9					262	51			5.35	1.88		
32	425	43.30	1.0	296	45			4.73	2.5						
38	366	37.30	1.15	347	39			4.04	3.5						
40	344	35.07	1.23	378	36			3.70	4.0						
46	296	30.18	1.43	431	31			3.25	5.5						
52	265	26.97	1.60	455	30			3.08	6.1						
53	258	26.31	1.64	519	26			2.70	7.8						
56	245	24.99	1.72	576	23			2.43	8.6						
64	215	21.93	1.96												
75	183	18.60	2.3	309	44			4.53	1.77	RX 67 RXF67	4 4				
83	165	16.79	2.6	326	41			4.30	1.82						
95	145	14.77	2.8	371	36			3.77	2.3						
100	137	13.95	2.9	438	31			3.20	3.1						
118	117	11.88	3.3	484	28			2.89	3.6						
38	355	36.93	0.8	551	24	2.54	4.5	RX 57 RXF57	4 4						
40	334	34.73	0.84	583	23	2.40	5.0								
47	287	29.88	0.98	686	20	2.04	6.4								
52	257	26.70	1.1	753	18	1.86	6.6								
59	227	23.59	1.2	870	15	1.61	6.9								
60	224	23.28	1.26	1000	13	1.40	7.3								
64	210	21.81	1.34												
73	185	19.27	1.50	369	36	3.79	1.78					RX 47 RF47	4 4		
78	172	17.89	1.58	394	34	3.55	1.90								
86	156	16.22	1.66	446	30	3.14	2.0								
96	140	14.56	1.8	481	28	2.91	2.3								
112	121	12.54	1.9	530	25	2.64	2.6								
119	113	11.79	2.0	591	23	2.37	2.8								
138	98	10.15	2.1	686	20	2.04	3.3								
154	87	9.07	2.2	729	18	1.92	3.5								
175	77	8.01	2.2	848	16	1.65	4.1								
180	75	7.76	2.4	946	14	1.48	4.5								
201	67	6.96	2.5	1077	13	1.30	4.7								
233	58	6.00	2.5												
248	54	5.64	2.7												
289	47	4.85	3.0												
323	42	4.34	3.3												
366	37	3.83	3.7												

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
2.2kW						2.2kW					
0.85	21991	1670	0.8	R 167R97 RF 167R97	4 4	5.8	3414	245.50	1.18	R 107 RF 107	4 4
0.98	19173	1456	0.88			6.3	3145	226.11	1.29		
1.1	17066	1296	1.0			7.1	2744	200.87	1.45		
1.2	14972	1137	1.1			8.5	2327	167.29	1.74		
1.4	13326	1012	1.27			9.1	2170	156.04	1.86		
1.6	11483	872	1.47			10	1940	139.47	2.1		
1.8	10140	770	1.67			11	1746	125.55	2.3		
2.1	8744	664	1.9			12	1581	113.70	2.6		
2.6	7111	540	1.72	R 147R87 RF 147R87	4 4	14	1402	100.82	2.9	R 97 RF 97	4 4
3.1	6084	462	2.0			16	1286	91.16	3.2		
3.3	5689	432	2.1			6.6	3003	215.94	0.94		
3.8	4912	373	2.5			7.6	2586	185.97	1.09		
4.3	4346	330	2.8			8.4	2351	169.06	1.20		
1.2	15354	1166	0.80	R 147R77 RF 147R77	4 4	9.4	2097	150.78	1.34	R 87 RF 87	4 4
1.4	13550	1029	0.90			11	1763	126.75	1.60		
1.6	11707	889	1.04			12	1620	116.48	1.74		
1.8	10324	784	1.18			14	1439	103.44	1.96		
2.0	9152	695	1.34			15	1286	92.48	2.2		
2.3	7993	607	1.53			17	1156	83.15	2.4		
2.6	7203	547	1.70			20	1004	72.17	2.8		
3.0	6321	480	1.93			22	906	65.12	3.1		
1.9	9721	730	0.77	R 137R77 RF 137R77	4 4	24	832	59.84	3.4	R 77 RF 77	4 4
2.1	9108	684	0.83			27	739	53.14	3.8		
2.3	8376	629	0.90			30	661	47.51	4.3		
2.4	7923	595	0.95			11	1738	124.97	0.84		
2.6	7311	549	1.03			12	1647	118.43	0.88		
2.9	6525	490	1.15			14	1442	103.65	1.01		
3.3	5699	428	1.32			15	1299	93.38	1.12		
3.8	4980	374	1.51	R 107R77 RF 107R77	4 4	17	1139	81.92	1.28		
4.5	4221	317	1.78			20	1007	72.37	1.45		
5.0	3808	286	1.97			22	883	63.50	1.65		
5.6	3377	250	2.2			24	837	60.18	1.74		
6.4	2958	219	2.5			27	733	52.67	1.99		
3.9	4822	357	0.84			30	660	47.45	2.2		
4.4	4336	321	0.93			34	579	41.63	2.5		
4.5	4228	313	0.96	R 97R57 RF 97R57	4 4	39	511	36.73	2.9	R 137 RF 137	8 8
5.1	3741	277	1.08			41	478	34.34	3.0		
5.5	3458	256	1.17			44	453	32.57	3.2		
6.7	2809	208	1.44			45	434	31.22	3.4		
6.0	3125	234	0.90			51	387	27.81	3.8		
6.7	2791	209	1.01	R 107 RF 107	6 6	61	325	23.40	4.5		
3.2	6212	223.34	1.21			66	299	21.51	4.7		
3.8	5234	188.16	1.43			22	915	65.77	0.8	R 77 RF 77	4 4
4.1	4851	174.4	1.55			25	784	56.38	1.0		
4.5	4348	156.31	1.73			28	708	50.90	1.1		
5.0	3925	141.12	1.92			32	623	44.78	1.2		
5.5	3565	128.18	2.1			34	588	42.29	1.31		
6.2	3163	113.72	2.4			39	501	36.01	1.54		
6.9	2871	103.2	2.6			43	455	32.72	1.69		
4.7	4220	200.87	0.96	R 107 RF 107	6 6	50	394	28.35	1.95		
5.6	3515	167.29	1.15			58	343	24.67	2.1		
6.0	3278	156.04	1.23			61	325	23.37	2.4		
6.7	2930	139.47	1.38			66	298	21.43	2.6		
						76	261	18.80	2.8		
						80	248	17.82	3.0		
						91	217	15.60	3.2		
						101	195	14.05	3.5		

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p				
2.2kW						2.2kW									
36	555	39.88	0.98	R 67 RF 67	4	300	69	4.73	1.69	RX 77 RXF 77	4				
38	522	37.50	1.03			351	59	4.04	2.3						
44	449	32.27	1.13			384	54	3.70	2.7						
49	401	28.83	1.22			437	47	3.25	3.6						
61	326	23.44	1.61			461	45	3.08	4.1						
71	277	19.89	2.0			526	39	2.70	5.2						
79	250	17.95	2.2			584	35	2.43	5.7						
90	220	15.79	2.4			667	31	2.13	6.1						
95	207	14.91	2.5			755	27	1.88	6.4						
112	177	12.70	2.8			850	24	1.67	6.7						
123	160	11.54	2.9	R 57 RF 57	4	1000	21	1.42	7.1	RX 67 RXF 67	4				
142	139	10.00	3.2			377	55	3.77	1.50						
163	121	8.70	3.4			444	46	3.20	2.0						
182	108	7.79	3.3			491	42	2.89	2.4						
38	519	37.30	0.82			559	37	2.54	3.0						
40	488	35.07	0.87			592	35	2.40	3.3						
47	420	30.18	1.01			696	30	2.04	4.3						
53	375	26.97	1.13			763	27	1.86	4.4						
65	305	21.93	1.39			882	23	1.61	4.6						
76	259	18.60	1.64			1014	20	1.40	4.8						
85	234	16.79	1.81	R 47 RF 47	4	452	46	3.14	1.34	RX 57 RXF 57	4				
96	205	14.77	1.99			538	38	2.64	1.69						
102	194	13.95	2.1			599	34	2.37	1.89						
120	165	11.88	2.3			696	30	2.04	2.2						
132	150	10.79	2.4			740	28	1.92	2.3						
152	130	9.35	2.7			861	24	1.65	2.7						
157	126	9.06	2.8			959	21	1.48	3.0						
178	111	7.97	3.0			1092	19	1.30	3.1						
74	268	19.27	1.03			R 37 RF 37	4	3.0kW							
88	226	16.22	1.15					1.2	20417			1137	0.83	R 167R97 RF 167R97	4
98	203	14.56	1.23	1.4	18172			1012	0.93						
113	174	12.54	1.35	1.6	15658			872	1.08						
120	164	11.79	1.40	1.8	13827			770	1.22						
140	141	10.15	1.53	2.1	11923			664	1.42						
157	126	9.07	1.64	2.8	9158			510	1.85						
177	111	8.01	1.73	2.6	9697			540	1.26	R 147R87 RF 147R87	4				
183	108	7.76	1.42	3.1	8296			462	1.47						
204	97	6.96	1.54	3.3	7757			432	1.58						
237	83	6.00	1.76	3.8	6698			373	1.82						
252	78	5.64	1.86	4.3	5926			330	2.1						
293	67	4.85	2.1	5.0	5082			283	2.4						
327	60	4.34	2.3	R 27 RF 27	4	1.6	15963	889	0.8	R 147R77 RF 147R77	4				
371	53	3.83	2.5			1.8	14078	784	0.87						
91	217	15.60	0.87			2.0	12480	695	0.98						
107	184	13.25	0.97			2.3	10900	607	1.12						
120	165	11.83	1.05			2.6	9822	547	1.24						
140	141	10.11	1.14			2.7	9388	517	0.80	R 137R77 RF 137R77	4				
150	132	9.47	1.19			2.9	8898	490	0.85						
178	111	7.97	1.32			3.1	8226	453	0.91						
213	93	6.67	1.46			3.3	7772	428	0.97						
250	79	5.67	1.69			3.8	6791	374	1.11						
281	70	5.06	1.80			4.5	5756	317	1.31						
329	60	4.32	2.0			5.0	5193	286	1.45						
351	56	4.05	2.0			5.7	4540	250	1.66						
416	47	3.41	2.2			6.5	3977	219	1.89						
140	141	10.13	0.81	R 107R77 RF 107R77	4	5.6	4798	253	0.84	R 107R77 RF 107R77	4				
215	92	6.59	1.09			5.8	4647	245	0.87						
254	78	5.60	1.19			6.8	3945	208	1.02						
284	70	5.00	1.28			7.8	3433	181	1.18						
333	59	4.27	1.38												
355	56	4.00	1.44												
421	47	3.37	1.58												

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
3.0kW						3.0kW					
3.2	8472	223.34	0.89	R 137 RF137	8	32	849	44.78	0.91	R 77 RF77	4
3.8	7137	188.16	1.05			34	802	42.29	0.96		
4.1	6615	174.40	1.14			39	683	36.01	1.13		
4.5	5929	156.31	1.27			43	621	32.72	1.24		
5.0	5353	141.12	1.40			50	538	28.35	1.43		
5.5	4862	128.18	1.55			58	468	24.67	1.57		
6.2	4314	113.72	1.74			61	443	23.37	1.74		
6.9	3914	103.20	1.92			66	406	21.43	1.90		
8.0	3364	88.70	2.20	R 137 RF137	8	76	357	18.80	2.1	R 77 RF77	4
						80	338	17.82	2.2		
						91	296	15.60	2.4		
						101	266	14.05	2.5		
						115	234	12.33	2.8		
						131	206	10.88	3.0		
						147	183	9.64	3.2		
						169	160	8.42	3.7		
				R 107 RF107	6	187	144	7.59	4.0	R 67 RF67	4
						213	126	6.66	4.3		
						61	445	23.44	1.18		
						71	377	19.89	1.50		
						79	340	17.95	1.63		
						90	299	15.79	1.76		
						95	283	14.91	1.8		
						112	241	12.70	2.0		
				R 107 RF107	4	123	219	11.54	2.1	R 57 RF57	4
						142	190	10.00	2.3		
						53	511	26.97	0.8		
						65	416	21.93	1.02		
						76	353	18.60	1.20		
						85	318	16.79	1.33		
						96	280	14.77	1.46		
						102	265	13.95	1.53		
				R 97 RF97	4	120	225	11.88	1.69	R 47 RF47	4
						132	205	10.79	1.79		
						152	177	9.35	2.0		
						157	172	9.06	2.1		
						178	151	7.97	2.2		
						189	143	7.53	2.3		
						222	122	6.41	2.6		
						244	110	5.82	2.7		
				R 87 RF87	4	281	96	5.05	3.0	R 37 RF37	4
						323	83	4.39	3.2		
						88	308	16.22	0.84		
						98	276	14.56	0.90		
						113	238	12.54	0.99		
						120	224	11.79	1.03		
						140	192	10.15	1.12		
						157	172	9.07	1.20		
				R 87 RF87	4	177	152	8.01	1.27	R 37 RF37	4
						183	147	7.76	1.04		
						204	132	6.96	1.13		
						237	114	6.00	1.29		
						252	107	5.64	1.36		
						293	92	4.85	1.53		
						327	82	4.34	1.67		
						371	73	3.83	1.86		
				R 87 RF87	4	140	192	10.11	0.83	R 37 RF37	4
						150	180	9.47	0.87		
						178	151	7.97	0.97		
						213	126	6.67	1.07		
						250	108	5.67	1.24		
						281	96	5.06	1.32		
						329	82	4.32	1.45		
						351	77	4.05	1.49		
				R 87 RF87	4	416	65	3.41	1.63		

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p		
3.0kW						4.0kW							
254	106	5.60	0.88	R 27 RF27	4	3.8	8877	376	0.85	R 137R77 RF137R77	4		
284	95	5.00	0.94			3.9	8830	374	0.85				
333	81	4.27	1.01			4.2	8004	339	0.94				
355	76	4.00	1.05			4.5	7484	317	1.00				
421	64	3.37	1.2			4.8	7012	297	1.07				
109	258	6.47	4.31	RX 127 RXF127	8	5.0	6752	286	1.11	R 107R77 RF107R77	4		
220	127	6.44	1.42	RX 87 RXF87	4	5.8	5902	250	1.27				
256	110	5.55	1.92			6.6	5171	219	1.45				
281	100	5.05	2.3			7.5	4509	191	0.90				
316	89	4.50	3.1			8.0	4273	181	0.95				
376	75	3.78	3.8			8.6	3943	167	1.03				
300	94	4.73	1.24	RX 77 RXF77	4	4.4	8152	163.46	1.50	R 147 RF147	8		
351	80	4.04	1.68			4.9	7324	146.85	1.67				
384	73	3.70	1.97			6.0	5946	119.24	2.0				
437	64	3.25	2.7			6.5	5487	110.03	2.2				
461	61	3.08	3.0			4.1	8698	174.40	0.86	R 137 RF137	8		
377	75	3.77	1.10	4.6	7796	156.31	0.96						
444	63	3.20	1.49	5.1	7038	141.12	1.07						
491	57	2.89	1.74	5.6	6393	128.18	1.18						
559	50	2.54	2.2	6.3	5671	113.72	1.33						
592	47	2.40	2.4	RX 67 RXF67	4	7.0	5147	103.20	1.46	R 137 RF137	6		
696	40	2.04	3.1			4.3	8354	223.34	0.90				
763	37	1.86	3.2			5.1	7038	188.16	1.07				
882	32	1.61	3.4			5.5	6523	174.40	1.15				
1014	28	1.40	3.5			6.1	5847	156.31	1.29				
452	62	3.14	0.98	RX 57 RXF57	4	6.8	5278	141.12	1.42	R 137 RF137	6		
538	52	2.64	1.24			7.5	4794	128.18	1.57				
599	47	2.37	1.38			8.4	4254	113.72	1.77				
696	40	2.04	1.61			9.3	3860	103.2	1.95				
740	38	1.92	1.71			11	3318	88.70	2.3				
861	33	1.65	1.99	RX 57 RXF57	4	9	4172	167.29	0.97	R 137 RF137	6		
959	29	1.48	2.2			5.1	7038	188.16	1.07				
1092	26	1.30	2.3			5.5	6523	174.40	1.15				
						6.1	5847	156.31	1.29				
						6.8	5278	141.12	1.42				
						7.5	4794	128.18	1.57				
						8.4	4254	113.72	1.77				
						9.3	3860	103.2	1.95				
						11	3318	88.70	2.3				
						9	4172	167.29	0.97	R 107 RF107	4		
						10	3891	156.04	1.04				
						11	3478	139.47	1.16				
						12	3131	125.55	1.29				
						13	2835	113.70	1.43				
						14	2514	100.82	1.61	R 107 RF107	4		
						16	2273	91.16	1.78				
						19	1927	77.26	2.1				
						20	1795	72.00	2.3				
						22	1616	64.81	2.5				
						25	1464	58.69	2.8	R 107 RF107	4		
						28	1298	52.05	3.1				
						12	2905	116.48	0.97				
						14	2579	103.44	1.09				
						16	2306	92.48	1.22				
						17	2073	83.15	1.36	R 97 RF97	4		
						20	1800	72.17	1.57				
						22	1624	65.12	1.74				
						24	1492	59.84	1.89				
						27	1325	53.14	2.1				
						30	1185	47.51	2.4	R 97 RF97	4		
						34	1065	42.72	2.6				
						39	925	37.08	3.0				
						43	828	33.20	3.2				
						45	803	32.22	3.3				
						54	669	26.84	3.6	R 147R77 RF147R77	4		
						58	624	25.03	4.3				
						64	558	22.37	4.6				
						71	502	20.14	4.9				
						78	455	18.24	6.2				

输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p					
4.0kW						4.0kW										
23	1583	63.5	0.92	R 87 RF87	4	142	253	10.15	0.85	R 47 RF47	4					
24	1501	60.18	0.97			159	226	9.07	0.86							
27	1313	52.67	1.11			180	200	8.01	0.91							
30	1183	47.45	1.23			207	174	6.96	0.96							
35	1038	41.63	1.40			240	150	6.00	0.98							
39	916	36.73	1.59			255	141	5.64	1.04							
42	856	34.34	1.70			297	121	4.85	1.17							
44	812	32.57	1.79			332	108	4.34	1.27							
46	779	31.22	1.87			376	96	3.83	1.42							
52	694	27.84	2.1								RX 127 RXF 127	8				
53	693	27.81	2.2			109	344	6.47	3.23							
62	584	23.40	2.5			121	310	5.88	3.59							
67	536	21.51	2.7								RX 127 RXF 127	6				
75	476	19.10	3.1			147	254	6.47	4.37							
84	426	17.08	3.1								RX 87 RXF87	4				
94	383	15.35	3.3			259	144	5.55	1.46							
108	332	13.33	3.6			285	131	5.05	1.78							
121	297	11.93	3.9			320	117	4.50	2.3							
						381	98	3.78	2.9							
40	898	36.01	0.86	R 77 RF77	4	356	105	4.04	1.28	RX 77 RXF77	4					
44	816	32.72	0.94			389	96	3.70	1.50							
51	707	28.35	1.09			443	84	3.25	2.0							
58	615	24.67	1.19			468	80	3.08	2.3							
62	583	23.37	1.32			533	70	2.70	2.9							
67	534	21.43	1.44			593	63	2.43	3.2							
77	469	18.80	1.56			676	55	2.13	3.4							
81	444	17.82	1.65			766	49	1.88	3.6							
92	389	15.60	1.79			862	43	1.67	3.7							
102	350	14.05	1.93			1014	37	1.42	3.9							
117	307	12.33	2.1								RX 67 RXF67	4				
132	271	10.88	2.3			450	83	3.20	1.13							
149	240	9.64	2.5			498	75	2.89	1.33							
171	210	8.42	2.8			567	66	2.54	1.68							
190	189	7.59	3.0			600	62	2.40	1.85							
216	166	6.66	3.3			706	53	2.04	2.4							
245	147	5.88	3.5			R 67 RF67	4	774	48	1.86	2.4	RX 57 RXF57	4			
276	130	5.21	3.7					894	42	1.61	2.6					
								1029	36	1.40	2.7					
72	496	19.89	1.14													
80	448	17.95	1.24	545	69			2.64	0.95							
91	394	15.79	1.34	608	62			2.37	1.05							
97	372	14.91	1.39	706	53			2.04	1.22							
113	317	12.70	1.54	750	50			1.92	1.30							
125	288	11.54	1.63	873	43			1.65	1.51							
144	249	10.00	1.77	973	38			1.48	1.66							
166	217	8.70	1.91	1108	34			1.30	1.75							
185	194	7.79	1.84						R 167R97 RF167R97	4						
196	184	7.36	1.90													
230	156	6.27	2.0													
253	142	5.70	2.1													
292	123	4.93	2.2													
336	107	4.29	2.4													
								5.5kW								
77	464	18.60	0.91	R 57 RF57	4	2.2	21556	664	0.80	R 147R87 RF147R87	4					
86	419	16.79	1.01			2.5	18764	578	0.90							
97	368	14.77	1.11			2.8	16556	510	1.02							
103	348	13.95	1.16			3.3	14219	438	1.19							
121	296	11.88	1.29			3.8	12336	380	1.37							
133	269	10.79	1.36			4.3	10973	338	1.54							
154	233	9.35	1.49			4.7	9966	307	1.70							
159	226	9.06	1.56			5.1	9155	282	1.85							
181	199	7.97	1.68									R 147R87 RF147R87	4			
191	188	7.53	1.75			3.1	14998	462	0.81							
225	160	6.41	1.97			3.3	14024	432	0.87							
247	145	5.82	2.1			3.9	12109	373	1.01							
285	126	5.05	2.3			4.4	10713	330	1.14							
328	109	4.39	2.4			5.1	9187	283	1.33							
						5.8	8116	250	1.51							
						6.7	7012	216	1.74							
						7.5	6201	191	1.97							

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
5.5kW						5.5kW					
3.7	12752	196.41	1.32	R 167 RF 167	8	45	1105	32.22	2.2	R 97 RF 97	4
4.5	10440	160.80	1.63			54	920	26.84	2.6		
5.5	8469	130.44	1.99			58	858	25.03	3.1		
6.0	7855	120.99	2.17			64	767	22.37	3.3		
6.9	6779	104.41	2.50			71	691	20.14	3.6		
						79	625	18.24	3.8		
						89	554	16.17	4.1		
4.4	10613	163.46	1.15	R 147 RF 147	8	30	1627	47.45	0.90	R 87 RF 87	4
4.9	9534	146.85	1.28			35	1427	41.63	1.02		
6.0	7742	119.24	1.57			39	1259	36.73	1.16		
6.6	7144	110.03	1.72			44	1117	32.57	1.30		
5.9	7960	163.46	1.54	R 147 RF 147	6	52	955	27.84	1.53		
6.5	7151	146.85	1.71			53	954	27.81	1.53		
8.0	6133	119.24	2.0			62	802	23.40	1.82		
8.8	5659	110.03	2.2			67	738	21.51	2.0		
10	4865	94.60	2.5			75	655	19.10	2.1		
12	4293	83.47	2.8			84	586	17.08	2.2		
5.6	8790	128.18	0.86	R 137 RF 137	8	94	526	15.35	2.4		
6.3	7798	113.72	0.96			108	457	13.33	2.6		
7.0	7077	103.2	1.06			121	409	11.93	2.8		
8.1	6083	88.70	1.24			145	339	9.90	3.3		
5.5	8970	174.40	0.84	R 137 RF 137	6	156	317	9.25	3.6		
6.1	8039	156.31	0.94			173	285	8.32	3.8		
6.8	7258	141.12	1.04			199	248	7.22	4.1		
7.5	6592	128.18	1.14			77	645	18.80	1.14	R 77 RF 77	4
8.4	5849	113.72	1.29			81	611	17.82	1.20		
9.3	5308	103.20	1.42			92	535	15.60	1.30		
6.4	7658	223.34	0.98	R 137 RF 137	4	102	482	14.05	1.40		
7.7	6451	188.16	1.17			117	423	12.33	1.53		
8.3	5980	174.40	1.26			132	373	10.88	1.66		
9.2	5359	156.31	1.40			149	331	9.64	1.79		
10	4839	141.12	1.55			171	289	8.42	2.1		
11	4395	128.18	1.71			190	260	7.59	2.2		
13	3899	113.72	1.93			216	228	6.66	2.4		
14	3538	103.20	2.1			245	202	5.88	2.52		
16	3041	88.70	2.5			276	179	5.21	2.68		
18	2774	80.91	2.7			91	541	15.79	0.97	R 67 RF 67	4
20	2520	73.49	3.0			97	511	14.91	1.01		
22	2236	65.20	3.4			113	435	12.70	1.12		
24	2029	59.17	3.7			125	396	11.54	1.19		
28	1744	50.86	4.3			144	343	10.00	1.29		
11	4305	125.55	0.94	R 107 RF 107	4	166	298	8.70	1.34		
13	3898	113.70	1.04			185	267	7.79	1.38		
14	3457	100.82	1.17			196	252	7.36	1.39		
16	3126	91.16	1.29			230	215	6.27	1.44		
19	2649	77.26	1.54			253	195	5.70	1.49		
20	2469	72.00	1.64			292	169	4.93	1.61		
22	2222	64.84	1.82			336	147	4.29	1.73		
25	2012	58.69	2.01			97	506	14.77	0.81	R 57 RF 57	4
28	1785	52.05	2.3			103	478	13.95	0.85		
31	1614	47.06	2.5			121	407	11.88	0.93		
36	1367	39.88	3.0			133	370	10.79	0.99		
17	2851	83.15	0.99	R 97 RF 97	4	154	321	9.35	1.08		
20	2475	72.17	1.14			181	273	7.97	1.22		
22	2233	65.12	1.26			191	258	7.53	1.27		
24	2052	59.84	1.37			225	220	6.41	1.43		
27	1822	53.14	1.55			247	200	5.82	1.51		
30	1629	47.51	1.73			285	173	5.05	1.66		
34	1465	42.72	1.93			328	151	4.39	1.75		
39	1271	37.08	2.2			297	166	4.85	0.85	R 47 RF 47	4
43	1138	33.20	2.4			332	149	4.34	0.92		
52	944	27.54	2.7			376	131	3.83	1.03		

输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p
5.5kW						7.5kW					
116	443	6.22	3.79	RX 157 RXF 157	8 8	4.4	14408	330	0.85	R 147R87 RF 147R87	4 4
123	420	5.88	2.64	RX 127 RXF 127	8 8	5.2	12356	283	0.99		
147	350	6.47	3.18	RX 127 RXF 127	6 6	5.8	10915	250	1.12		
164	315	5.88	3.53			6.8	9431	216	1.30		
182	283	5.28	3.92			7.6	8339	191	1.47		
217	238	6.65	1.82	RX 107 RXF 107	4 4	9.1	7030	161	1.74		
257	200	5.60	2.14			3.7	18366	196.41	0.92	R 167 RF 167	8 8
277	186	5.19	3.52			4.5	15036	160.80	1.13		
310	166	4.65	3.93			5.5	12197	130.44	1.39		
247	208	5.82	1.9	6.0	11314	120.99	1.50				
297	173	4.85	2.1	6.9	9763	104.41	1.73				
319	162	4.52	3.5	RX 97 RXF 97	4 4	4.9	13775	196.41	1.23		
356	144	4.04	3.9			6.0	11277	160.80	1.50		
396	130	3.64	4.3			7.4	9145	130.44	1.84		
436	118	3.30	4.7			7.9	8485	120.99	1.99		
493	104	2.92	5.4			9.2	7323	104.41	2.31		
545	94	2.64	5.9			10	6462	92.14	2.6		
643	80	2.24	7.0			12	5602	79.88	3.0		
735	70	1.96	7.6			14	4984	71.07	3.4		
878	59	1.64	8.1			15	4487	63.98	3.8		
1014	51	1.42	8.4			16	4103	58.51	4.1		
320	161	4.50	1.7	RX 87 RXF 87	4 4	4.4	15285	163.46	0.80	R 147 RF 147	8 8
381	135	3.78	2.1			4.9	13732	146.85	0.89		
414	124	3.48	3.1			6.0	11150	119.24	1.09		
466	110	3.09	3.4			6.6	10289	110.03	1.20		
522	99	2.76	3.9			5.9	11464	163.46	1.07	R 147 RF 147	6 6
581	89	2.48	4.3			6.5	10299	146.85	1.19		
670	77	2.15	4.7			8.0	8363	119.24	1.45		
443	116	3.25	1.47			8.8	7717	110.03	1.59		
468	110	3.08	1.65	10	6635	94.60	1.84	R 137 RF 137	4 4		
533	97	2.70	2.1	12	5854	83.47	2.1				
593	87	2.43	2.3	7.7	8677	188.16	0.87				
676	76	2.13	2.5	8.4	8042	174.40	0.94				
766	67	1.88	2.6	9.3	7208	156.31	1.04				
862	60	1.67	2.7	10	6508	141.12	1.16				
1014	51	1.42	2.9	11	5911	128.18	1.27				
567	91	2.54	1.22	13	5244	113.72	1.43				
600	86	2.40	1.35	14	4759	103.20	1.58				
706	73	2.04	1.73	16	4090	88.70	1.84				
774	66	1.86	1.78	18	3731	80.91	2.0				
894	58	1.61	1.86	20	3389	73.49	2.2				
1029	50	1.40	2.0	22	3007	65.20	2.5				
706	73	2.04	0.89	25	2729	59.17	2.8	R 107 RF 107	4 4		
750	69	1.92	0.95	29	2345	50.86	3.2				
873	59	1.65	1.10	16	4204	91.16	0.96				
973	53	1.48	1.21	19	3563	77.26	1.13				
1108	46	1.30	1.27	20	3320	72.00	1.22				
7.5kW						23	2989			64.81	1.35
2.9	22268	510	0.80	25	2706	58.69	1.49				
3.3	19124	438	0.88	28	2400	52.05	1.68				
3.8	16591	380	1.02	31	2170	47.06	1.86				
4.3	14758	338	1.15	37	1839	39.88	2.2				
4.8	13404	307	1.26	42	1607	34.84	2.5				
5.2	12313	282	1.37	48	1404	30.44	2.9				
						50	1344			29.14	3.0
						54	1257			27.25	3.2
						59	1134			24.60	3.6
						65	1030			22.34	3.9

输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p
7.5kW						7.5kW					
24	2760	59.84	1.02	R 97 RF 97	4 4	123	572	5.88	2.94	RX 127	6
27	2451	53.14	1.15			136	515	5.28	3.26	RXF 127	6
31	2191	47.51	1.29			167	420	4.29	4.0		
34	1970	42.72	1.43								
39	1710	37.08	1.65			221	318	6.47	3.49	RX 127	4
44	1531	33.20	1.72			245	286	5.88	3.88	RXF 127	4
45	1486	32.22	1.77								
53	1270	27.54	1.94			220	320	6.65	1.35	RX 107 RXF 107	4 4
54	1238	26.84	1.98			260	269	5.60	1.59		
58	1154	25.03	2.30			281	250	5.19	2.6		
65	1032	22.37	2.48	314	224	4.65	2.9				
72	929	20.14	2.64								
80	841	18.24	2.79								
40	1694	36.73	0.86	R 87 RF 87	4 4	251	280	5.82	1.41	RX 97 RXF 97	4 4
45	1502	32.57	0.97			301	233	4.85	1.59		
52	1284	27.84	1.1			323	217	4.52	2.6		
53	1282	27.81	1.13			361	194	4.04	2.9		
62	1079	23.40	1.35			401	175	3.64	3.2		
68	992	21.51	1.42			442	159	3.30	3.5	RX 87 RXF 87	4 4
76	881	19.10	1.54			500	140	2.92	4.0		
85	788	17.08	1.66			324	216	4.50	1.26		
95	708	15.35	1.78			386	182	3.78	1.58		
110	615	13.33	1.96			420	167	3.48	2.3		
122	550	11.93	2.1	472	149	3.09	2.6	RX 87 RXF 87	4 4		
147	457	9.90	2.4	529	133	2.76	2.9				
158	427	9.25	2.7	589	119	2.48	3.2				
175	384	8.32	2.8	679	103	2.15	3.5				
202	333	7.22	3.0	756	93	1.93	3.6				
226	298	6.47	3.2								
272	247	5.36	3.5								
78	867	18.80	0.85	R 77 RF 77	4 4	449	156	3.25	1.09	RX 77 RXF 77	4 4
82	822	17.82	0.89			474	148	3.08	1.23		
94	719	15.60	0.97			541	130	2.70	1.56		
104	648	14.05	1.04			601	117	2.43	1.73		
118	569	12.33	1.14			685	102	2.13	1.84		
134	502	10.88	1.24			777	90	1.88	1.94	RX 67 RXF 67	4 4
151	445	9.64	1.33			874	80	1.67	2.0		
173	388	8.42	1.53			1028	68	1.42	2.1		
192	350	7.59	1.64								
219	307	6.66	1.78			575	122	2.54	0.91		
248	271	5.88	1.87	608	115	2.40	1.00	RX 67 RXF 67	4 4		
280	240	5.21	2.00	716	98	2.04	1.28				
				785	89	1.86	1.32				
				907	77	1.61	1.38				
				1043	67	1.40	1.45				
115	586	12.70	0.83	R 67 RF 67	4 4	11kW					
127	532	11.54	0.88			4.9	18891	295	0.90	R 167R107 RF 167R107	4 4
146	461	10.00	0.96			5.1	18379	287	0.92		
168	401	8.70	0.99			5.2	17994	281	0.94		
187	359	7.79	1.02			6.1	15241	238	1.11		
198	339	7.36	1.03			7.0	13320	208	1.27		
233	289	6.27	1.07			8.3	11271	176	1.50		
256	263	5.70	1.11							R 167R97 RF 167R97	4 4
296	227	4.93	1.20			4.3	21645	338	0.80		
340	198	4.29	1.28			4.8	19659	307	0.86		
				5.2	18059	282	0.94				
183	368	7.97	0.91	R 57 RF 57	4 4	5.8	16009	250	0.80	R 147R87 RF 147R87	4 4
194	347	7.53	0.95			6.8	13832	216	0.88		
228	296	6.41	1.07			7.6	12231	191	1.00		
251	268	5.82	1.12			9.1	10310	161	1.19		
289	233	5.05	1.23			9.2	10182	159	1.20		
333	202	4.39	1.30								
123	572	5.88	1.94	RX 127 RXF 127	8 8						
156	449	6.22	3.74	RX 157 RXF 157	6 6						

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
11kW						11kW					
6.0	16540	160.80	1.02	R 167 RF 167	6	135	732	10.83	2.7	R 97 RF 97	4
7.4	13417	130.44	1.26		6	158	626	9.26	3.0		4
7.9	12445	120.99	1.36		6	174	566	8.37	3.4		4
9.2	10740	104.41	1.58		6	206	480	7.09	3.9		4
						235	419	6.20	4.2		
7.4	13284	196.41	1.27	R 167 RF 167	4	68	1455	21.51	0.97	R 87 RF 87	4
9.1	10876	160.80	1.56		4	76	1292	19.10	1.05		4
11	8822	130.44	1.91		4	85	1155	17.08	1.13		4
12	8183	120.99	2.07		4	95	1038	15.35	1.21		4
14	7062	104.41	2.4		4	110	902	13.33	1.33		4
16	6232	92.14	2.7		4	122	807	11.93	1.43		4
18	5403	79.88	3.1		4	147	670	9.90	1.66		4
21	4807	71.07	3.5		4	158	626	9.25	1.82		4
6.5	15105	146.85	0.81	R 147 RF 147	6	175	563	8.32	1.94	RX 157 RXF 157	6
8.1	12265	119.24	1.0		6	202	488	7.22	2.1		6
8.7	11318	110.03	1.08		6	226	438	6.47	2.2		6
10	9731	94.60	1.26		6	272	363	5.36	2.4		6
12	8586	83.47	1.42			134	736	10.88	0.84	R 77 RF 77	4
8.9	11056	163.46	1.11	R 147 RF 147	4	151	652	9.64	0.91		4
10	9932	146.85	1.23		4	192	513	7.59	1.12		4
12	8065	119.24	1.52		4	219	450	6.66	1.21		4
13	7442	110.03	1.64		4	248	398	5.88	1.28		4
15	6398	94.60	1.91		4	280	352	5.21	1.36		
17	5645	83.47	2.2		4	191	539	5.05	3.12	RX 157 RXF 157	6
20	4876	72.09	2.5		4	209	492	4.68	3.41		6
22	4508	66.65	2.7		4	240	429	4.04	3.92		6
24	4129	61.50	3.0			235	437	6.22	3.84	RX 157 RXF 157	4
28	3576	52.87	3.4								4
10	9545	141.12	0.80	R 137 RF 137	4	249	414	5.88	2.68	RX 127 RXF 127	4
11	8669	128.18	0.87		4	277	372	5.28	2.98		4
13	7691	113.72	0.98		4	339	304	4.29	3.65		4
14	6980	103.2	1.08		4	372	277	3.95	4.01		4
16	5999	88.70	1.25		4	281	366	5.19	1.79	RX 107 RXF 107	4
18	5472	80.91	1.37		4	314	328	4.65	1.99		4
20	4970	73.49	1.51		4	348	296	4.20	2.63		4
22	4410	65.20	1.71		4	383	269	3.81	2.90		4
25	4002	59.17	1.88		4	432	238	3.38	3.27		4
29	3440	50.86	2.2		4	476	216	3.07	3.60		4
33	3002	44.39	2.5			553	186	2.64	4.19		
39	2540	37.65	3.0			323	319	4.52	1.75	RX 97 RXF 97	4
44	2226	32.91	3.4			361	285	4.04	1.96		4
23	4383	64.81	0.92	R 107 RF 107	4	401	257	3.64	2.2		4
25	3969	58.69	1.02		4	442	233	3.30	2.4		4
28	3520	52.05	1.15		4	500	206	2.92	2.7		4
31	3183	47.06	1.27		4	553	186	2.64	3.0		4
37	2697	39.88	1.50		4	652	158	2.24	3.5		4
42	2356	34.84	1.72		4	745	138	1.96	3.9		4
48	2059	30.44	1.96		4	890	116	1.64	4.1		4
50	1971	29.14	2.1		4	1028	100	1.42	4.3		4
54	1843	27.25	2.2			420	245	3.48	1.55	RX 87 RXF 87	4
59	1664	24.60	2.4			472	218	3.09	1.75		4
65	1511	22.34	2.7			529	195	2.76	1.96		4
74	1341	19.82	3.0			589	175	2.48	2.2		4
81	1217	17.99	3.3			679	152	2.15	2.4		4
34	2889	42.72	0.98	R 97 RF 97	4	756	136	1.93	2.5		4
39	2508	37.08	1.12		4	913	113	1.60	2.6		
44	2245	33.20	1.21		4	1050	98	1.39	2.8		
53	1863	27.54	1.35		4	601	171	2.43	1.18	RX 77 RXF 77	4
58	1693	25.03	1.57		4	685	150	2.13	1.25		4
65	1513	22.37	1.69		4	777	133	1.88	1.33		4
72	1362	20.14	1.80		4	874	118	1.67	1.38		4
80	1234	18.24	1.90		4	1028	100	1.42	1.46		4
90	1094	16.17	2.1		4						
100	989	14.62	2.2								
118	838	12.39	2.5								

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
15kW						15kW					
6.1	20783	238	0.81	R 167R107 RF167R107	4	53	2540	27.54	1.1	R 97 RF97	4
6.5	19560	224	0.87			58	2309	25.03	1.15		
7.0	18163	208	0.93			65	2063	22.37	1.24		
7.5	17028	195	0.99			72	1858	20.14	1.32		
8.3	15369	176	1.10			80	1682	18.24	1.40		
7.4	18201	130.44	0.93	R 167 RF167	6	90	1491	16.17	1.51	R 87 RF87	4
8.0	16883	120.99	1.00			100	1348	14.62	1.6		
9.2	14569	104.41	1.16			118	1143	12.39	1.8		
11	12857	92.14	1.32			135	999	10.83	2.0		
7.4	18115	196.41	0.93	R 167 RF167	4	158	854	9.26	2.4	RX 157 RXF157	4
9.1	14830	160.80	1.14			174	772	8.37	2.5		
11	12030	130.44	1.41			206	654	7.09	2.9		
12	11159	120.99	1.52			235	572	6.20	3.1		
14	9630	104.41	1.76			85	1575	17.08	0.89		
16	8498	92.14	1.99			95	1416	15.35	0.98		
18	7367	79.88	2.3			110	1229	13.33	1.05		
21	6555	71.07	2.6			122	1100	11.93	1.13		
23	5901	63.98	2.9			147	913	9.90	1.21		
25	5396	58.51	3.1			158	853	9.25	1.33		
8.8	15353	110.03	0.80	R 147 RF147	6	175	767	8.32	1.42	RX 127 RXF127	4
10	13200	94.60	0.93			202	666	7.22	1.51		
12	11647	83.47	1.05			226	597	6.47	1.61		
13	10059	72.09	1.21			272	494	5.36	1.73		
14	9300	66.65	1.31	R 147 RF147	4	287	488	5.05	3.44	RX 107 RXF107	4
8.9	15076	163.46	0.81			315	446	4.68	3.77		
9.9	13544	146.85	0.90			361	388	4.04	3.32		
12	10997	119.24	1.11			372	378	3.95	2.94		
13	10148	110.03	1.20			281	479	5.19	1.36		
15	8725	94.60	1.40			314	429	4.65	1.52		
17	7698	83.47	1.59			348	387	4.20	2.0		
20	6649	72.09	1.84			383	351	3.81	2.2		
22	6147	66.65	1.99			432	325	3.38	2.4		
24	5631	61.50	2.2			476	295	3.07	2.6		
28	4876	52.87	2.5			553	254	2.64	3.1		
31	4303	46.65	2.8			635	221	2.30	3.5		
14	9518	103.2	0.8	R 137 RF137	4	749	188	1.95	3.8	RX 97 RXF97	4
16	8181	88.70	0.92			854	164	1.71	4.0		
18	7462	80.91	1.01			1014	138	1.44	4.4		
20	6778	73.49	1.11			323	435	4.52	1.3		
22	6013	65.20	1.25			361	388	4.04	1.4		
25	5457	59.17	1.38			401	350	3.64	1.6		
29	4691	50.86	1.60			442	317	3.30	1.8		
33	4094	44.39	1.84			500	281	2.92	2.0		
39	3472	37.65	2.2			553	254	2.64	2.2		
44	3035	32.91	2.5			652	215	2.24	2.6		
52	2567	27.83	2.9			745	188	1.96	2.8		
31	4340	47.06	0.9	R 107 RF107	4	890	158	1.64	3.0	RX 87 RXF87	4
37	3678	39.88	1.10			1028	137	1.42	3.1		
42	3213	34.84	1.26			420	335	3.48	1.14		
50	2688	29.14	1.50			472	297	3.09	1.28		
48	2807	30.44	1.44			529	265	2.76	1.43		
54	2513	27.25	1.61			589	238	2.48	1.60		
59	2269	24.60	1.78			679	207	2.15	1.75		
65	2060	22.34	1.96			756	186	1.93	1.80		
74	1828	19.82	2.2			913	154	1.60	1.92		
81	1659	17.99	2.4			1050	134	1.39	2.0		
94	1426	15.46	2.8								
108	1245	13.50	3.2								

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p						
18.5kW						18.5kW											
9.1	18291	160.80	0.93	R 167 RF167	4	110	1516	13.33	0.8	R 87 RF87	4						
11	14838	130.44	1.13			122	1357	11.93	0.85								
12	13763	120.99	1.24			147	1126	9.90	0.98								
14	11877	104.41	1.42			158	1052	9.25	1.08								
16	10481	92.14	1.61			175	946	8.32	1.15								
18	9086	79.88	1.86			202	821	7.22	1.22								
21	8084	71.07	2.1			226	736	6.47	1.30								
23	7278	63.98	2.3			272	610	5.36	1.40								
25	6655	58.51	2.5														
29	5791	50.91	2.9														
12	13564	119.24	0.90	R 147 RF147	4	317	547	4.68	3.07	RX 157 RXF157	4						
13	12516	110.03	0.98			364	476	4.04	3.53								
15	10761	94.60	1.14			412	420	3.57	4.0								
17	9495	83.47	1.29			348	478	4.20	1.63								
20	8200	72.09	1.49			383	452	3.81	1.73								
22	7581	66.65	1.61			432	401	3.38	1.95								
24	6944	61.50	1.76			476	364	3.07	2.1								
28	6014	52.87	2.0			553	313	2.64	2.5								
31	5306	46.65	2.3			635	273	2.30	2.9								
36	4583	40.29	2.7			749	231	1.95	3.1								
18	9203	80.91	0.82	R 137 RF137	4	854	203	1.71	3.3	RX 107 RXF107	4						
20	8359	73.49	0.90			1014	171	1.44	3.6								
22	7416	65.20	1.01														
25	6731	59.17	1.12			401	432	3.64	1.30								
29	5785	50.86	1.30			442	391	3.30	1.43								
33	5049	44.39	1.49			500	346	2.92	1.62								
39	4283	37.65	1.76			553	313	2.64	1.79								
44	3744	32.91	2.0			652	266	2.24	2.1								
49	3362	29.56	2.2			745	232	1.96	2.3								
52	3166	27.83	2.3			890	194	1.64	2.4								
61	2730	24.00	2.7	1028	168	1.42	2.5	529	327	2.76	1.16	RX 97 RXF97	4				
66	2520	22.15	3.0					589	294	2.48	1.29						
77	2166	19.04	3.5					679	255	2.15	1.42						
87	1911	16.80	3.9					756	229	1.93	1.46						
37	4536	39.88	0.89	R 107 RF107	4	913	190	1.60	1.56	RX 87 RXF87	4						
42	3963	34.84	1.02			1050	165	1.39	1.65					589	294	2.48	1.29
50	3315	29.14	1.22											679	255	2.15	1.42
59	2798	24.60	1.44											756	229	1.93	1.46
65	2541	22.34	1.59											913	190	1.60	1.56
74	2255	19.82	1.79											1050	165	1.39	1.65
81	2046	17.99	1.98														
94	1759	15.46	2.3														
108	1536	13.50	2.6														
128	1302	11.45	3.1														
146	1139	10.01	3.5	R 97 RF97	4	22kW						R 167 RF167	4				
181	918	8.07	3.0			11	17645	130.44	0.95								
213	778	6.84	3.6			12	16366	120.99	1.04								
72	2291	20.14	1.07			14	14124	104.41	1.20								
80	2075	18.24	1.13			16	12464	92.14	1.36								
90	1839	16.17	1.23			18	10805	79.88	1.57								
100	1663	14.62	1.30			21	9614	71.07	1.76								
118	1409	12.39	1.46			23	8655	63.98	2.0								
135	1232	10.83	1.59			25	7915	58.51	2.1								
158	1053	9.26	1.81			29	6887	50.91	2.5								
174	952	8.37	2.0	32	6078	44.93	2.8										
206	806	7.09	2.3	37	5269	38.95	3.2	13	14884	110.03	0.83	R 147 RF147	4				
235	705	6.20	2.5					15	12797	94.60	0.95						
282	589	5.18	2.8					17	11291	83.47	1.08						
325	511	4.49	3.0					20	9752	72.09	1.3						
								22	9016	66.65	1.36						
								24	8258	61.50	1.48						
								28	7152	52.87	1.71						
								31	6310	46.65	1.94						
								36	5450	40.29	2.2						
								41	4821	35.64	2.5						
								49	4051	29.95	3.0						

输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p		
22kW						22kW							
22	8820	65.20	0.85	R 137 RF137	4	652	316	2.24	1.77	RX 97 RXF97	4		
25	8004	59.17	0.94			745	276	1.96	1.94				
29	6880	50.86	1.09			890	231	1.64	2.05				
33	6005	44.39	1.25			1028	200	1.42	2.14				
39	5093	37.65	1.48			R 87 RXF87	4	529	389	2.76	0.98		
44	4452	32.91	1.69					589	350	2.48	1.09		
49	3999	29.56	1.88					679	303	2.15	1.19		
52	3765	27.83	2.00					756	272	1.93	1.23		
61	3246	24.00	2.3					913	226	1.60	1.31		
66	2996	22.15	2.5					1050	196	1.39	1.39		
77	2576	19.04	2.9										
87	2273	16.80	3.3										
101	1963	14.51	3.8										
114	1736	12.83	4.3										
30kW						30kW							
42	4713	34.84	0.86	R 107 RF107	4	16	16996	92.14	1.0	R 167 RF167	4		
50	3942	29.14	1.03			18	14735	79.88	1.15				
59	3328	24.60	1.21			21	13109	71.07	1.29				
65	3022	22.34	1.34			23	11802	63.98	1.43				
74	2681	19.82	1.51			25	10793	58.51	1.57				
81	2434	17.99	1.66			29	9391	50.91	1.80				
94	2091	15.46	1.93			32	8288	44.93	2.04				
108	1826	13.50	2.2			37	7185	38.95	2.4				
128	1549	11.45	2.6			42	6393	34.66	2.6				
146	1354	10.01	2.6			49	5510	29.87	3.1				
173	1144	8.46	3.0			60	4477	24.27	3.8				
181	1092	8.07	3.0			71	3796	20.58	4.5				
213	925	6.84	3.5			R 147 RF147	4	17	15397	83.47	0.8		
244	809	5.98	3.5					20	13298	72.09	0.92		
72	2724	20.14	1.04	22	12294			66.65	0.99				
80	2467	18.24	1.14	24	11261			61.50	1.09				
90	2187	16.17	1.23	28	9752			52.87	1.25				
100	1978	14.62	1.29	31	8605			46.65	1.42				
118	1676	12.39	1.34	36	7432			40.29	1.64				
135	1465	10.83	1.43	41	6574			35.64	1.86				
158	1253	9.26	1.52	49	5525			29.95	2.2				
174	1132	8.37	1.69	60	4462			24.19	2.5				
206	959	7.09	1.96	71	3770			20.44	3.0				
235	839	6.20	2.1	81	3328			18.04	3.0				
282	701	5.18	2.4	93	2885			15.64	4.2				
325	607	4.49	2.5	R 137 RF137	4			29	9382	50.86	0.80		
147	1339	9.90	0.83			33	8188	44.39	0.92				
158	1251	9.25	0.91			39	6945	37.65	1.08				
175	1125	8.32	0.97			44	6071	32.91	1.24				
202	977	7.22	1.03			52	5133	27.83	1.41				
226	875	6.47	1.10			61	4427	24.00	1.69				
272	725	5.36	1.18			66	4086	22.15	1.85				
412	500	3.57	3.36			RX 157 RXF157	4	77	3512	19.04	2.1		
								87	3099	16.80	2.4		
								101	2676	14.51	2.8		
								114	2367	12.83	3.2		
348	592	4.20	1.32			RX 107 RXF107	4	135	1990	10.79	3.8		
383	537	3.81	1.45					192	1400	7.59	3.4		
432	477	3.38	1.64					229	1177	6.38	4.1		
476	433	3.07	1.80	R 107 RF107	4			74	3656	19.82	1.11		
553	372	2.64	2.10					81	3318	17.99	1.22		
635	324	2.30	2.41					94	2852	15.46	1.42		
749	275	1.95	2.61					108	2490	13.50	1.62		
854	241	1.71	2.75					128	2112	11.45	1.88		
1014	203	1.44	2.99					146	1846	10.01	1.91		
401	513	3.64	1.09					RX 97 RXF97	4	173	1561	8.46	2.2
										181	1489	8.07	2.2
										213	1262	6.84	2.5
										244	1103	5.98	2.6
										289	933	5.06	2.9
						442	465			3.30	1.20		
500	412	2.92	1.36										
553	372	2.64	1.50										

输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p		
30kW						37kW							
100	2697	14.62	0.80	R 97 RF97	4	39	8507	37.65	0.88	R 137 RF137	4		
118	2285	12.39	0.90			45	7436	32.91	1.01				
135	1998	10.83	0.98			53	6288	27.83	1.20				
158	1708	9.26	1.12			61	5423	24.00	1.38				
174	1544	8.37	1.24			67	5005	22.15	1.51				
206	1308	7.09	1.44			77	4302	19.04	1.75				
235	1144	6.20	1.55			88	3796	16.80	1.98				
282	955	5.18	1.75			101	3279	14.51	2.3				
325	828	4.49	1.85			115	2899	12.83	2.6				
432	649	3.40	1.71	RX 127 RXF127	4	136	2438	10.79	2.8	R 107 RF107	4		
476	566	3.07	1.38	RX 107 RXF107	4	169	1968	8.71	3.1				
553	487	2.64	1.60			194	1715	7.59	3.3				
635	424	2.30	1.84			230	1442	6.38	3.7				
749	360	1.95	2.0			285	1164	5.15	3.7				
854	315	1.71	2.1			74	4478	19.82	0.90				
1014	266	1.44	2.3			82	4065	17.99	0.99				
500	539	2.92	1.04	RX 97 RXF97	4	95	3493	15.46	1.16				
553	487	2.64	1.15			109	3050	13.50	1.33				
652	413	2.24	1.35			128	2587	11.45	1.5				
745	362	1.96	1.48			147	2262	10.01	1.56				
890	303	1.64	1.57			174	1912	8.46	1.79				
1028	262	1.42	1.63			182	1823	8.07	1.8				
						215	1546	6.84	2.1				
				246	1351	5.98	2.1						
				291	1143	5.06	2.4						
37kW						432	801	3.40	1.39	RX 127 RXF127	4		
18	18049	79.88	0.94	R 167 RF167	4	490	707	3.00	1.57	RX 107 RXF107	4		
21	16058	71.07	1.05			568	610	2.59	1.82				
23	14456	63.98	1.17			435	796	3.38	0.98				
25	13220	58.51	1.28			479	723	3.07	1.08				
29	11503	50.91	1.47			557	622	2.64	1.25				
33	10152	44.93	1.67			639	542	2.30	1.44				
38	8801	38.95	1.92			754	459	1.95	1.57				
42	7831	34.66	2.16			860	403	1.71	1.65				
49	6749	29.87	2.5			1021	339	1.44	1.79				
61	5484	24.27	3.1			45kW							
78	4232	18.73	4.0			23	17463	63.98	0.97			R 167 RF167	4
90	3685	16.31	4.6			25	15970	58.51	1.06				
101	3290	14.56	5.1			29	13896	50.91	1.22				
22	15060	66.65	0.81	33	12264	44.93	1.38						
24	13794	61.50	0.89	38	10631	38.95	1.59						
28	11946	52.87	1.02	43	9460	34.66	1.79						
32	10541	46.65	1.16	50	8153	29.87	2.08						
36	9104	40.29	1.34	61	6624	24.27	2.4						
41	8053	35.64	1.52	72	5617	20.58	2.6						
49	6767	29.95	1.81	79	5112	18.73	3.0						
61	5466	24.19	2.0	91	4452	16.31	3.4						
72	4618	20.44	2.4	102	3974	14.56	3.5						
81	4076	18.04	2.4	28	14431	52.87	0.85	R 147 RF147	4				
94	3534	15.64	3.5	32	12733	46.65	0.96						
106	3143	13.91	3.8	37	10997	40.29	1.11						
				42	9728	35.64	1.26						
				49	8175	29.95	1.49						
				61	6603	24.19	1.69						
				72	5579	20.44	2.0						
				82	4924	18.04	2.0						
				95	4269	15.64	2.9						
				106	3797	13.91	3.2						
				123	3273	11.99	3.7						
				204	1979	7.25	4.1						

输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output touque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p		
45kW						55kW							
45	8983	32.91	0.84	R 137 RF137	4	78	6352	19.04	1.18	R 137 RF137	4		
53	7596	27.83	0.99			88	5605	16.80	1.34				
62	6551	24.00	1.15			102	4841	14.51	1.55				
67	6046	22.15	1.24			115	4280	12.83	1.76				
78	5197	19.04	1.45			137	3600	10.79	1.90				
88	4586	16.80	1.64			170	2906	8.71	2.1				
102	3960	14.51	1.90			195	2532	7.59	2.3				
115	3502	12.83	2.1			232	2128	6.38	2.5				
137	2945	10.79	2.3			287	1718	5.15	2.5				
170	2377	8.71	2.6										
195	2072	7.59	2.8			415	1242	3.57	1.35	RX 157	4		
232	1741	6.38	3.1			479	1075	3.09	1.56	RXF157	4		
287	1406	5.15	3.1										
						75kW							
96	4220	15.46	0.96	R 107 RF107	4	38	17719	38.95	0.95	R 167 RF167	4		
110	3685	13.50	1.10			43	15767	34.66	1.07				
129	3125	11.45	1.27			50	13588	29.87	1.25				
148	2732	10.01	1.29			61	11041	24.27	1.43				
175	2309	8.46	1.48			72	9362	20.58	1.53				
183	2203	8.07	1.50			79	8521	18.73	1.81				
216	1867	6.84	1.71			91	7420	16.31	2.03				
247	1632	5.98	1.75			102	6624	14.56	2.13				
292	1381	5.06	2.0			119	5646	12.41	3.0				
						144	4677	10.28	3.4				
435	968	3.40	1.15	RX 127 RXF127	4	169	3990	8.77	4.0				
493	854	3.00	1.30										
571	737	2.59	1.51			49	13625	29.95	0.90	R 147 RF147	4		
646	652	2.29	1.70			61	11004	24.19	1.11				
767	549	1.93	2.02	72	9298	20.44	1.20						
						82	8207	18.04	1.21				
438	962	3.38	0.81	RX 107 RXF107	4	95	7115	15.64	1.72				
482	874	3.07	0.89			106	6328	13.91	1.87				
561	751	2.64	1.04			123	5454	11.99	2.2				
643	654	2.30	1.19			152	4431	9.74	2.5				
759	555	1.95	1.30			179	3758	8.26	2.8				
865	487	1.71	1.36			204	3298	7.25	3.0				
1028	410	1.44	1.48			251	2679	5.89	3.3				
						296	2275	5.00	3.6				
						479	1466	3.09	1.15	RX 157 RXF157	4		
29	16984	50.91	1.00	538	1304	2.75	1.29						
33	14989	44.93	1.13	624	1124	2.37	1.49						
38	12984	38.95	1.30	767	915	1.93	1.84						
43	11563	34.66	1.46	R 167 RF167	4	767	915	1.93	1.21	RX 127	4		
50	9963	29.87	1.70			949	740	1.56	1.50	RXF127	4		
61	8097	24.27	1.96										
72	6866	20.58	2.09										
79	6248	18.73	2.50										
91	5441	16.31	2.76										
102	4857	14.56	2.90										
119	4140	12.41	4.09										
144	3429	10.28	4.66										
						90kW							
32	15563	46.65	0.8			R 147 RF147	4	43	18921	34.66	0.89	R 167 RF167	4
37	13441	40.29	0.91					50	16306	29.87	1.04		
42	11890	35.64	1.03					61	13249	24.27	1.20		
49	9991	29.95	1.22	72	11235			20.58	1.28				
61	8070	24.19	1.39	79	10225			18.73	1.51				
72	6819	20.44	1.64	91	8904			16.31	1.69				
82	6018	18.04	1.65	102	7948			14.56	1.77				
95	5218	15.64	2.3	119	6775			12.41	2.5				
106	4640	13.91	2.6	144	5612			10.28	2.8				
123	4000	11.99	3.1	169	4788			8.77	3.3				
152	3249	9.74	3.8										
204	2419	7.25	3.4										
251	1965	5.89	4.1										


输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
90kW											
72	11158	20.44	1.01								
82	9848	18.04	1.10								
95	8538	15.64	1.43								
106	7593	13.91	1.56	R 147	4						
123	6545	11.99	1.87	RF 147	4						
156	5170	9.47	2.1								
179	4509	8.26	2.4								
204	3958	7.25	2.5								
251	3215	5.89	2.7								
296	2729	5.00	3.0								
542	1555	2.75	1.08	RX 157	4						
629	1340	2.37	1.25	RXF157	4						
772	1091	1.93	1.54								
955	882	1.56	1.26	RX 127	4						
				RXF127	4						
110kW											
61	16193	24.27	1.04								
72	13731	20.58	1.23								
91	10882	16.31	1.38	R 167	4						
102	9715	14.56	1.45	RF 167	4						
119	8280	12.41	2.04								
144	6859	10.28	2.3								
169	5851	8.77	2.7								
629	1638	2.37	1.03	RX 157	4						
772	1334	1.93	1.26	RXF157	4						
914	1126	1.63	1.49								
132kW											
72	16477	20.58	1.03								
91	13059	16.31	1.15	R 167	4						
102	11657	14.56	1.21	RF 167	4						
119	9936	12.41	1.70								
144	8231	10.28	1.94								
169	7022	8.77	2.28								
914	1351	1.63	1.24	RX 157	4						
				RXF157	4						
160kW											
120	11963	12.41	1.41	R 167	4						
145	9910	10.28	1.61	RF 167	4						
170	8484	8.77	1.89								

Mamax Permissible Rorque Nm	输出转速 Output speed r/min	传动比 Ratio i	机型号 Type Type	功 率 Power kW/4p	Mamax Permissible Rorque Nm	输出转速 Output speed r/min	传动比 Ratio i	机型号 Type Type	功 率 Power kW/4p	
130	8.5	164	R 27R17 RF 27R17	0.18	1550	0.91	1524	R 87R57 RF 87R57	0.18	
	8.9	156				0.93	1489		0.25	
	10	135				1.0	1395			
	12	118		1.1		1232				
	13	104		1.2		1145	0.37			
15	90	1.3	1037							
200	4.8	289	R 37R17 RF 37R17	0.18		1.6			883	0.37
	5.7	243				1.7	802			
	6.2	226				1.8	754			
	8.5	164		0.25		1.4	1008		0.55	
	8.9	156				2.0	683			
	10	135				2.3	599			
	11	127				2.6	538			
13	104	2.9	472							
15	90									
300	3.2	429	R 47R37 RF 47R37	0.18	3.4	400	0.75			
	3.7	372			3.5	396				
	4.0	348			3.9	361				
	4.6	301		4.0	351	1.1				
	5.5	255		4.6	305					
6.1	228	4.7	300							
450	2.1	678	R 57R37 RF 57R37	0.18	5.2	267	0.18			
	2.4	589			5.5	256				
	2.6	537			0.32	4309				
	3.0	471		0.35	4004					
	3.9	357		0.38	3702					
	4.4	319		0.40	3481					
600	5.2	267	R 67R37 RF 67R37	0.25	0.46	3019	0.25			
	5.8	241			0.52	2668				
	1.7	836			0.62	2245				
	1.9	750		0.69	2016	0.37				
	2.0	730		0.76	1823					
	2.2	630		0.80	1733					
	2.4	571		0.86	1623					
	2.5	561		0.88	1583					
	2.8	495		0.97	1434					
	2.9	486		1.00	1396					
	3.2	438								
3.6	388									
820	4.1	336	R 77R37 RF 77R37	0.37	1.1	1228	R 97R57 RF 97R57	0.55		
	4.8	287			1.2	1207				
	1.2	1124			1.3	1084				
	1.3	1047		1.4	1068					
	1.5	915		1.5	934					
	1.6	858		1.6	878	0.75				
	1.8	757		1.7	824					
	2.1	671		1.8	755					
	2.4	571		1.9	737	1.1				
	2.5	547		2.1	631					
	2.9	477		2.2	625					
	3.3	426		2.4	560					
	3.8	364		2.5	549					
	1550	4.5		312	R 87R57 RF 87R57	0.55		2.9	484	2.2
4.6		310	3.2	430						
5.6		248	3.7	379						
0.65		2129	4.1	336						
0.71		1955	4.7	296						
0.72		1930	5.1	270						
0.79		1737	5.6	249						
0.80		1733	5.9	234						
				6.1	227					


Mamax Permissible Rorque Nm	输出转速 Output speed r/min	传动比 Ratio i	机型号 Type Type	功 率 Power kW/4p	Mamax Permissible Rorque Nm	输出转速 Output speed r/min	传动比 Ratio i	机型号 Type Type	功 率 Power kW/4p			
4300	0.21	6690	R 107R77 RF 107R77	0.18	8000	0.35	4018	R 137R77 RF 137R77	0.37			
	0.24	5735				0.36	3928					
	0.27	5127				0.40	3514					
	0.32	4302				0.41	3377					
	0.36	3870				0.42	3338					
	0.36	3847		0.25		0.47	2929		0.55			
	0.42	3302				0.48	2926					
	0.45	3015				0.52	2658					
	0.46	2997				0.56	2484					
	0.53	2621				0.58	2412					
	0.62	2252		0.37		0.62	2242		0.75			
	0.68	2041				0.67	2073					
	0.71	1971				0.75	1863					
	0.77	1813				0.76	1839					
	0.83	1673		0.55		0.88	1598		1.1			
	0.88	1587				1.0	1397					
	0.91	1531				1.1	1226					
	1.00	1390				1.2	1170					
	1.14	1216		0.75		1.3	1080		1.5			
	1.2	1194				1.4	1020					
	1.27	1095				1.5	951					
	1.3	1043				1.6	869					
	1.50	927				1.7	831					
	1.6	888		1.1		2.0	730		2.2			
	1.7	787				2.1	684					
	2.0	692				2.3	629					
	2.2	605				2.4	609					
	2.3	598		1.5		2.5	564		3			
	2.6	530				2.6	549					
	2.7	510				2.8	517					
	2.9	479				2.9	490					
	3.1	463				3.2	453					
	3.4	420		2.2		3.4	428		4			
	3.5	406				3.6	388					
	3.8	373				3.8	376					
	4.0	357				4.2	339					
	4.5	321				4.5	317					
	4.6	313		3		4.8	297		5.5			
	5.1	281				5.0	286					
	5.2	277				5.8	250					
	5.7	253				0.08	18210			0.18		
	5.8	245				0.09	15923					
	6.6	217		4		4			0.10		14075	
	6.9	208							0.12		12344	
	7.9	191							0.13		11143	
	7.5	181		0.18		0.18			0.15	9743	0.25	
	8.6	167							0.17	8443		
8000	0.12	11712	R 137R77 RF 137R77	0.18	13000	0.19	7479	R 147R77 RF 147R77	0.37			
	0.13	10573				0.20	7307					
	0.16	8784				0.22	6447					
	0.19	7479		0.25		0.26	5568		0.55			
	0.22	6412				0.30	4815					
	0.24	5834				0.33	4325					
	0.28	5001		0.37		0.39	3669		0.75			
	0.30	4709				0.44	3228					
	0.32	4364				0.50	2833					

Mamax Permissible Rorque Nm	输出转速 Output speed r/min	传动比 Ratio i	机型号 Type Type	功 率 Power kW/4p	Mamax Permissible Rorque Nm	输出转速 Output speed r/min	传动比 Ratio i	机型号 Type Type	功 率 Power kW/4p					
13000	0.56	2555	R 147R77 RF 147R77	1.1	R 167R107 RF 167R107	4.9	295	11	15					
	0.65	2211				5.1	287							
	0.73	1951				5.2	281							
	0.84	1705		1.5		5.6	260							
	0.93	1536				6.1	238							
	1.1	1329				6.5	224							
	1.2	1166		2.2		7.0	208							
	1.4	1029				7.5	195							
	1.6	889												
	1.8	784		3										
	2.1	695												
	2.4	607										4		
	2.6	547												
	3.0	480		5.5										
	2.7	540										4		
	3.1	462												
	3.3	432		5.5										
	3.9	373										7.5		
4.4	330													
6.8	216	11												
18000	0.05		27001	R 167R97 RF 167R97	0.55									
	0.06		22482											
	0.07	20002												
	0.08	17361												
	0.09	15446												
	0.10	14051												
	0.12	11812												
	0.13	10509												
	0.14	9754												
	0.23	6069												
	0.26	5399	0.75											
	0.30	4709												
	0.33	4182												
	0.18	7749	1.1											
	0.20	6894												
	0.37	3739												
	0.54	2657	1.5											
	0.61	2333												
	0.69	2085												
	0.76	1877	2.2											
	0.86	1670												
	0.98	1456												
	1.1	1296	3											
	1.3	1137												
	1.4	1012												
	1.7	872	4											
	1.9	770												
	2.2	664												
	2.5	578	5.5											
	2.8	510												
	3.3	438												
	3.8	380	7.5											
	4.3	338												
	4.8	307												
	5.2	282	11											


RX37




RX..S37



RXF37



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



注：其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机机座号 Motor size	63	71		80		90S	
功率/4P Power/(kw)	0.18	0.25	0.37	0.55	0.75	1.1	
L3	237	260		280		295	
G	130	145		175		195	
L2	65	65		85		85	


注：“RX..”表示RX.RXF

Note: “RX..”mean RX.RXF

RX57




RX..S57




RXF57


$\phi 140$




$\phi 160$



$\phi 200$



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



注: 其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机机座号 Motor size	63		71		80		90S	90L	100		112M	132S	
功率/4P Power/(kw)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5		
L3	237	260		280		295	320	355		365	430		
G	130	145		175		195	195	215		240	275		
L2	65	65		81		81	81	93		93	101		


注: "RX.."表示RX.RXF

Note: "RX.."mean RX.RXF




RX67




RX. . S67



RXF67



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



注: 其余尺寸见相应的结构形式


Note:For other values please refer to the oppsited structure

Y2电机机座号 Motor size	63	71		80		90S	90L	100		112M	132S	132M
功率/4P Power/(kw)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5
L3	237	260		280		295	320	355		365	430	470
G	130	145		175		195	195	215		240	275	275
L2	65	65		81		81	81	93		93	101	101


注：“RX..”表示RX.RXF

Note: "RX.."mean RX,RXF

RX77





RX..S77



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected

RXF77

 $\phi 200$  $\phi 250$ 

注：其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机座号 Motor size	90S	90L	100	112M	132S	132M	160M	
功率/4P Power/(kw)	1.1	1.5	2.2	3.0	4.0	5.5	7.5	11
L3	306	325	355	370	430	470	505	
G	195	195	215	240	275	275	335	
L2	81	81	93	93	101	101	126	


注：“RX..”表示RX.RXF

Note: “RX..”mean RX.RXF

RX87





RX. . S87




电机需方装配时或配特殊电机时需加联接法兰

when equipping the user's moto
or the special one,the flange is
required to connected

RXF87



Ø300



注：其余尺寸见相应的结构形式


Note:For other values please refer to the oppsited structure

Y2电机机座号 Motor size	100	112M	132S	132M	160M	160L	180M	180L	
功率/4P Power/(kw)	3.0	4.0	5.5	7.5	11	15	18.5	22	
L3	355	370	430	470	505	550	605	645	
G	215	240	275	275	335	335	380	380	
L2	93	93	101	101	126	126	126	126	


注：“RX..”表示RX.RXF

Note: "RX.."mean RX.RXF

RX97





RX..S97




电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected

RXF97



$\phi 350$




注：其余尺寸见相应的结构形式
Note:For other values please
refer to the oppsited structure


Y2电机机座号 Motor size	132S	132M	160M	160L	180M	180L	200	
功率/4P Power/(kw)	5.5	7.5	11	15	18.5	22	30	
L3	430	470	505	550	605	645	660	
G	275	275	335	335	380	380	420	
L2	86	86	108	108	108	108	150	

注：“RX..”表示RX.RXF
Note：“RX..”mean RX.RXF

RX107






RX..S107



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected

RXF107

 $\phi 450$ 

注：其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机座号 Motor size	132S	132M	160M	160L	180M	180L	200	225S	225M
功率/4P Power/(kw)	5.5	7.5	11	15	18.5	22	30	37	45
L3	430	470	505	550	605	645	660	680	705
G	275	275	335	335	380	380	420	475	475
L2	108	108	108	108	108	108	150	150	150


注：“RX..”表示RX.RXF

Note: “RX..”mean RX.RXF


RX127




RX..S127



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



RXF127



注：其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机机座号 Motor size	132M	160M	160L	180M	180L	200	225S	225M	250	280S	280M
功率/4P Power/(kw)	7.5	11	15	18.5	22	30	37	45	55	75	90
L3	470	505	550	605	645	660	680	705	790	845	845
G	275	335	335	380	380	420	475	475	510	580	580
L2	125	125	125	125	125	150	150	150	165	165	165


注：“RX..”表示RX.RXF

Note: “RX..”mean RX.RXF


RX157




RX..S157



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



RXF157



注：其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机机座号 Motor size	160M	160L	180M	180L	200	225S	225M	250	280S	280M	315S	315M
功率/4P Power/(kw)	11	15	18.5	22	30	37	45	55	75	90	110	132
L3	505	550	605	645	660	680	705	790	845	845	1100	1130
G	335	335	380	380	420	475	475	510	580	580	645	645
L2	125	125	125	125	150	150	150	165	165	165	190	190


注：“RX..”表示RX.RXF

Note: “RX..”mean RX.RXF


R17




R..S17



RF17



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



注：其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机机座号 Motor size	63	71	80		
功率/4P Power/(kw)	0.18	0.25	0.37	0.55	0.75
L3	237	260	280		
G	130	145	175		
L2	65	65	85		




注：“R..”表示R.R F

Note：“R..”mean R.RF


R27




RF27




R. . S27



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



R. . 27RF17



注：其余尺寸见相应的结构形式


Note:For other values please refer to the oppsited structure

Y2电机机座号 Motor size	63	71	80	90S	90L	100L	
功率/4P Power/(kw)	0.18	0.25 0.37	0.55 0.75	1.1	1.5	2.2 3.0	
L3	237	260	280	295	320	355	
G	130	145	175	195	195	215	
L2	65	65	85	85	85	95	


注：“R..”表示R.RF

Note: "R.."mean R.RF

R37




R..S37




RF37


$\phi 120$




$\phi 160$




$\phi 200$



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



R..37RF17



注：其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机座号 Motor size	63	71	80	90S	90L	100L	
功率/4P Power/(kw)	0.18	0.25 0.37	0.55 0.75	1.1	1.5	2.2 3.0	
L3	237	260	280	295	320	355	
G	130	145	175	195	195	215	
L2	65	65	85	85	85	95	


注：“R..”表示R.RF

Note：“R..”mean R.RF

R47




R..S47




RF47


$\phi 140$




$\phi 160$




$\phi 200$



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



R..47RF37



注：其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机座号 Motor size	63	71	80	90S	90L	100L	112M	132S	
功率/4P Power/(kw)	0.18	0.25 0.37	0.55 0.75	1.1	1.5	2.2 3.0	4	5.5	
L3	237	260	280	295	320	355	365	430	
G	130	145	175	195	195	215	240	275	
L2	65	65	81	81	81	93	93	101	

注：“R..”表示R.RF


Note:“R..”mean R.RF

R57




RF57


$\phi 160$




$\phi 200$




$\phi 250$




RM57




R..S57



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



R..57RF37



注：其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机座号 Motor size	63	71	80	90S	90L	100	112M	132S	132M
功率/4P Power/(kw)	0.18	0.25 0.37	0.55 0.75	1.1	1.5	2.2 3.0	4.0	5.5	7.5
L3	237	260	280	295	320	355	365	430	470
G	130	145	175	195	195	215	240	275	275
L2	65	65	81	81	81	93	93	101	101


注：“R..”表示R.RF

Note：“R..”mean R.RF


R67





R..S67




RF67




电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected

 $\phi 250$ 

R..67RF37



RM67



注：其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机机座号 Motor size	63		71		80		90S	90L	100		112M	132S	132M
功率/4P Power/(kw)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	
L3	237	260		280		295	320	355		365	430	470	
G	130	145		175		195	195	215		240	275	275	
L2	65	65		81		81	81	93		93	101	101	


注：“R..”表示R.RF

Note: “R..”mean R.RF

R77




R..S77




RF77


$\phi 250$




$\phi 300$




电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



R..77RF37



RM77



注：其余尺寸见相应的结构形式



Note:For other values please
refer to the oppsited structure

Y2电机座号 Motor size	63	71		80		90S	90L	100		112M	132S	132M	160M	
功率/4P Power/(kw)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	11	
L3	237	260		280		295	320	355		365	430	470	505	
G	130	145		175		195	195	215		240	275	275	335	
L2	65	65		81		81	81	93		93	101	101	126	

注：“R..”表示R.RF



Note：“R..”mean R.RF

R87





RF87



Ø300




Ø350




RM87




R. . S87



电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



R. . 87RF57



注: 其余尺寸见相应的结构形式


Note: For other values please refer to the oppsited structure

Y2电机机座号 Motor size	80		90S	90L	100		112M	132S	132M	160M	160L	180M	180L
功率/4P Power/(kw)	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	11	15	18.5	22
L3	280		295	320	355		365	430	470	505	550	605	645
G	175		195	195	215		240	275	275	335	335	380	380
L2	81		81	81	93		93	101	101	126	126	126	126


注：“R..”表示R.RF

Note: "R.."mean R.RF

R97




R..S97




RF97


Φ350




Φ450





电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



R.. 97RF57



RM97



注: 其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机座号 Motor size	80		90S	90L	100		112M	132S	132M	160M	160L	180M	180L	200
功率/4P Power/(kw)	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	11	15	18.5	22	30
L3	280		295	320	355		365	430	470	505	550	605	645	660
G	175		195	195	215		240	275	275	335	335	380	380	420
L2	86		86	86	86		86	86	86	108	108	108	108	150


注: "R.."表示R.RF

Note: "R.."mean R.RF

R107




R..S107




RF107


$\phi 350$




$\phi 450$




电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



R..107RF77



RM107



注：其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机座号 Motor size	100	112M	132S	132M	160M	160L	180M	180L	200	225S	225M	
功率/4P Power/(kw)	2.2	3.0	4.0	5.5	7.5	11	15	18.5	22	30	37	45
L3	355	365	430	470	505	550	605	645	660	680	705	
G	215	240	275	275	335	335	380	380	420	475	475	
L2	86	86	108	108	108	108	108	108	150	150	150	


注：“R..”表示R.RF

Note: “R..”mean R.RF



R137




R..S137




RF137

 $\phi 450$  $\phi 550$ 


电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



R.. 137RF77



RM137



注：其余尺寸见相应的结构形式


Note:For other values please
refer to the oppsited structure

Y2电机座号 Motor size	132S	132M	160M	160L	180M	180L	200	225S	225M	250	
功率/4P Power/(kw)	5.5	7.5	11	15	18.5	22	30	37	45	55	
L3	430	470	505	550	605	645	660	680	705	790	
G	275	275	335	335	380	380	420	475	475	510	
L2	125	125	125	125	125	125	150	150	150	165	


注：“R..”表示R.RF

Note:“R..”mean R.RF

R147




R..S147




RF147


φ450




φ550




电机需方装配时或配特殊电机时需加联接法兰
when equipping the user's moto
or the special one,the flange is
required to connected



R..147RF87(77)



RM147



R..147RF77

R..147RF87

L

220

272

注: 其余尺寸见相应的结构形式

Note:For other values please
refer to the oppsited structure

Y2电机座号 Motor size	160M	160L	180M	180L	200	225S	225M	250	280S	280M	
功率/4P Power/(kw)	11	15	18.5	22	30	37	45	55	75	90	
L3	505	550	605	645	660	680	705	790	845	845	
G	335	335	380	380	420	475	475	510	580	580	
L2	125	125	125	125	150	150	150	165	165	165	

注: "R.."表示R..RF

Note: "R.."mean R.RF